

Insulating and Splicing – Rubber Tapes

3M™ Temflex™ Rubber Splicing Tape 2155

3M™ Temflex™ Rubber Splicing Tape 2155 is a conformable self-fusing rubber electrical insulating tape. It is designed for low voltage electrical insulating and moisture sealing applications. Compatible with solid dielectric cable insulations, Temflex Tape 2155 is a self-fusing tape. Flexible over a wide temperature range, it is Underwriters Laboratories (UL) Listed for use up to 600 volts.

Liner/Linerless	Liner
Material	Ethylene Propylene Rubber (EPR)
Tape Grade	General Use
Tape Type	Insulating and Splicing
Operating Temperature	Up to 176°F (80°C)
RoHS 2011/65/EU	Yes
Agency Approvals	
Country of Origin	Brazil



Order No.	UPC	Color	Length	Width	Thickness	Breaking Strength	Rolls per Carton	Rolls per Case
2155-3/4X22FT	054007-50348	Black	22'	0.75"	30 mil	9 lbs/in	1	10
2155-3/4X22FT-20RLS	051138-97905	Black	22'	0.75"	30 mil	9 lbs/in	1	20
2155-1-1/2X22FT	054007-50349	Black	22'	1.50"	30 mil	9 lbs/in	1	45

Scotch® Self-Fusing Silicone Rubber Electrical Tape 70

Scotch® Self-Fusing Silicone Rubber Electrical Tape 70 is a high-temperature, arc- and track-resistant tape composed of self-fusing, inorganic silicone rubber with an easy-tear and easy-strip liner. Scotch® Self-Fusing Silicone Rubber Electrical Tape 70 can be used as base tape layer to cleanly reenter connections.

Material	Inorganic Silicone Rubber
Tape Grade	Premium
Tape Type	Insulating and Splicing
Operating Temperature	Up to 356°F (180°C)
RoHS 2011/65/EU	Yes
Specifications	AA-59163 Class-I Type I; ASTM D-1000-76; ASTM D-495-71
Country of Origin	Canada



Order No.	UPC	Color	Length	Width	Thickness	Elongation	Breaking Strength	Rolls per Carton	Rolls per Case
70-1x30FT	051128-57261	Sky Blue Gray	30'	1.00"	12 mil	450%	12 lbs/in	1	24