

Insulating and Splicing – Rubber Tapes

Scotch® Electrical Semi-Conducting Tape 13

Scotch® Electrical Semi-Conducting Tape 13 is a highly conformable, semi-conducting Ethylene Propylene Rubber (EPR)-based, high-voltage splicing tape. Scotch Electrical Tape 13 elongates easily to conform to irregular shapes and retains its conductivity when stretched.

Liner/Linerless	Liner
Material	Semi-Conducting Ethylene Propylene Rubber
Tape Grade	Premium
Tape Type	Insulating and Splicing
Operating Temperature	Up to 194°F (90°C)
Emergency Overload Temperature	266°F (130°C)
RoHS 2011/65/EU	Yes
Country of Origin	Brazil



Order No.	UPC	Color	Length	Width	Thickness	Elongation	Breaking Strength	Rolls per Case
13	051128-53115	Black	10'	0.75"	30 mil	800%	6 lbs/in	250
13-3/4X15FT	054007-15017	Black	15'	0.75"	30 mil	800%	6 lbs/in	50
13-1-1/2X15FT	054007-15017	Black	15'	1.5"	30 mil	800%	6 lbs/in	45

Scotch® Varnished Cambric Tape 2510

Scotch® Varnished Cambric Tape 2510 is made from straight-cut woven cotton cambric fabric. The fabric is oil primed and coated with a high-grade yellow electrical insulating varnish. Varnished cambric tapes are flexible, electrically insulating and moisture resistant with a smooth finish. Scotch Tape 2510 tape is yellow, non-adhesive coated and 7 mils thick, providing an excellent dielectric strength with high puncture and cut-through resistance. Its electrical properties are stable up to 105°C.

Material	Straight cut woven cotton cambric fabric with electrical insulating varnish
Tape Grade	Premium
Tape Type	Insulating and Splicing
Operating Temperature	Up to 220°F (105°C)
RoHS 2011/65/EU	Yes
Specifications	ASTM D-374; ASTM D-1000; ASTM D-295
Country of Origin	Pakistan



Order No.	UPC	Color	Length	Width	Thickness	Breaking Strength	Rolls per Carton	Rolls per Case
2510-3/4X60FT	054007-41720	Yellow	60'	0.75"	7 mil	50 lbs/in	1	20
2510-3/4X36YD	054007-10661	Yellow	36 yd	0.75"	7 mil	50 lbs/in	1	48
2510-1X36YD	054007-10687	Yellow	36 yd	1.00"	7 mil	50 lbs/in	1	36
2510-1-1/2X36YD	054007-10703	Yellow	36 yd	1.50"	7 mil	50 lbs/in	1	24
2510-2X36YD	054007-10711	Yellow	36 yd	2.00"	7 mil	50 lbs/in	1	16
2510-36X25YD	054007-15751	Yellow	25 yd	3.00"	7 mil	50 lbs/in	1	1