


Copper/Aluminum Connectors



PRODUCT REFERRAL GENERATOR

Cold Shrink Splicing	pg. 311
– QS-III Splices	
– 5750 and 5760 Series	
– 8420 Series	
Tape Splicing	pg. 353
– 5700 Series	
Resin Splicing	pg. 330
– 82-A Series	
– 82-F Series	



Specifications and Ordering Information for 3M™ Scotchlok™ Copper/Aluminum Connectors 20000 Series (AL9CU) up to 35 kV

Product Number	UPC (054007-)	Color Code	Wire Size	Dimensions		L	Minimum Order Case Qty.
				I.D.	O.D.		
20001	13236	Gray	6 AWG	0.200" (5,1 mm)	0.344" (8,8 mm)	1.620" (41,1 mm)	50 each
20002	13244	Green	4 AWG	0.265" (6,7 mm)	0.468" (11,8 mm)	1.880" (47,8 mm)	50 each
20003	13251	Pink	2 AWG	0.307" (7,8 mm)	0.531" (13,5 mm)	2.000" (50,8 mm)	25 each
20004	13269	Gold	1 AWG	0.350" (8,9 mm)	0.531" (13,5 mm)	2.000" (50,8 mm)	10 each
20005	13277	Tan	1/0 AWG	0.414" (10,5 mm)	0.640" (16,3 mm)	2.120" (53,8 mm)	10 each
20006	13285	Olive	2/0 AWG	0.439" (11,2 mm)	0.687" (17,4 mm)	2.310" (58,7 mm)	10 each
20007	13293	Ruby	3/0 AWG	0.484" (12,3 mm)	0.760" (19,3 mm)	2.620" (66,5 mm)	10 each
20008	13301	White	4/0 AWG	0.562" (14,3 mm)	0.875" (22,2 mm)	2.750" (69,9 mm)	10 each
20009	13319	Red	250 kcmil	0.594" (15,1 mm)	0.906" (23,0 mm)	2.940" (74,7 mm)	3 each
20010	13327	Dark Blue	300 kcmil (150 mm²)	0.650" (16,5 mm)	1.010" (25,6 mm)	3.120" (79,2 mm)	3 each
20011	13335	Brown	350 kcmil	0.720" (18,3 mm)	1.105" (28,1 mm)	3.380" (85,9 mm)	3 each
20012	13343	Green	400 kcmil	0.760" (19,3 mm)	1.187" (30,1 mm)	3.750" (95,3 mm)	3 each
20014	13350	Pink	500 kcmil	0.843" (21,4 mm)	1.320" (33,5 mm)	3.880" (98,6 mm)	3 each
20016	13368	Black	600 kcmil	0.923" (23,4 mm)	1.430" (36,3 mm)	4.120" (104,6 mm)	3 each
20019	13376	Yellow	750 kcmil	1.031" (26,2 mm)	1.594" (40,5 mm)	4.620" (117,3 mm)	3 each
20020	13384	Light Blue	800 kcmil	1.051" (26,7 mm)	1.655" (42,0 mm)	4.750" (120,7 mm)	3 each
20024	13392	Brown	1000 kcmil (500 mm²)	1.193" (30,3 mm)	1.843" (46,8 mm)	5.250" (133,4 mm)	3 each