

Screw cover enclosures with 1-2-3 hole openings

UL® Listed per UL 50 for industrial controls

Wallmount pushbutton enclosures are molded from gray, engineered thermoplastic material that is resistant to most corrosive agents. Universal pushbutton holes are designed to accommodate all standard oil-tight pushbuttons, switches and pilot lights. A grounding plate is included on the cover. Auxiliary devices must be rated for appropriate NEMA applications.

Features and benefits:

- 30.5mm keyed pushbutton holes*
- Material: nylon base and cover
- Integrally molded mounting flange
- Brass screw inserts
- 304 (18-8) stainless screws (8-32/3/16")
- Temperature range: -40° to 185°F
- UL94-V2



30.5mm pushbutton enclosures†

| Cat. No. | Style | Inside box size A x B x C | Mounting L x J | Overall outside including mounting bracket H x W x D | | | | F | G | R | S | Std. Ctn. | Std. Wt. (lbs.) |
|----------|----------------|------------------------------|-------------------|--|------|------|------|------|-----|-----|----|-----------|-----------------|
| | | | | H | W | D | | | | | | | |
| CP100N | One Opening | 3.13 x 2.81 x 3 | 4 x 2.38 | 4.88 | 3.50 | 3.38 | 3.38 | 3.25 | .63 | 2.5 | 12 | 9 | |
| CP200N | Two Openings | 5.38 x 2.81 x 3 | 6.25 x 2.38 | 7.13 | 3.50 | 3.38 | 5.63 | 3.25 | .63 | 2.5 | 8 | 8 | |
| CP300N | Three Openings | 7.38 x 2.81 x 3 | 8.50 x 2.38 | 9.38 | 3.50 | 3.38 | 7.88 | 3.25 | .63 | 2.5 | 6 | 7.60 | |

22mm pushbutton enclosures*†

| Cat. No. | Style | Inside box size A x B x C | Mounting L x J | Overall outside including mounting bracket H x W x D | | | | F | G | R | S | Std. Ctn. | Std. Wt. (lbs.) |
|----------|----------------|------------------------------|-------------------|--|------|------|------|------|-----|-----|----|-----------|-----------------|
| | | | | H | W | D | | | | | | | |
| PX0010 | One Opening | 3.13 x 2.81 x 3 | 4 x 2.38 | 4.88 | 3.50 | 3.38 | 3.38 | 3.25 | .63 | 2.5 | 10 | 8.26 | |
| PX0007 | Two Openings | 5.38 x 2.81 x 3 | 6.25 x 2.38 | 7.13 | 3.50 | 3.38 | 5.63 | 3.25 | .63 | 2.5 | 1 | 1.31 | |
| PX0011 | Three Openings | 7.38 x 2.81 x 3 | 8.50 x 2.38 | 9.38 | 3.50 | 3.38 | 7.88 | 3.25 | .63 | 2.5 | 6 | 9.43 | |
| PX0008 | Four Openings | 7.38 x 2.81 x 3 | 8.50 x 2.38 | 9.38 | 3.50 | 3.38 | 7.88 | 3.25 | .63 | 2.5 | 1 | 1.60 | |

* All Circuit Safe pushbutton enclosures are furnished with standard hole dimensions: 1 7/32" diameter with keyways at 12 o'clock and 3 o'clock

† Dimensions are in inches unless marked otherwise. Operators not included.

