

Sealed fittings

Straight fitting



Straight fitting - Sealed fittings

Straight compression type fitting incorporating fixed or swivel male threads to provide connection to knockouts and threaded entries. These fittings are designed for use with all types of unslit Harnessflex conduit, maintaining maximum conduit bore.

Straight (metric versions) - Sealed fittings

Straight body Part No.	Cap nut	Sealing bush	Conduit size		Thread size
			NC	NW	
AB12-M16	CN07	SRN07	10	8.5	M16 x 1.5mm
AB12-M20	CN07	SRN07	10	8.5	M20 x 1.5mm
AB12-M16	CN09	SRN09	12	10	M16 x 1.5mm
AB12-M20	CN09	SRN09	12	10	M20 x 1.5mm
AB16-M16	CN11	SRN11	16	13	M16 x 1.5mm
AB16-M20	CN11	SRN11	16	13	M20 x 1.5mm
AB20-M20	CN16	SRN16	20	17	M20 x 1.5mm
AB25-M25	CN21	SRN21	25	22	M25 x 1.5mm
AB25-M25	CN28	SRN28	28	23	M25 x 1.5mm
AB32-M32	CN32	SRN29	32	29	M32 x 1.5mm
AB40-M40	CN36	SRN36	40	36	M40 x 1.5mm
AB50-M50	CN48	SRN48	50	48	M50 x 1.5mm

NOTE: Order elbow bodies, cap nuts, sealing bushes separately

A	B	C	Min bore D	Thread E	A/F size F	G
34	12	23	11	M16 x 1.5mm	22	17
37	14	23	15	M20 x 1.5mm	27	17
34	12	26	11	M16 x 1.5mm	22	17
37	14	26	15	M20 x 1.5mm	27	17
35	12	26	11	M16 x 1.5mm	27	17
37	14	26	15	M20 x 1.5mm	27	11
39	14	31	15	M20 x 1.5mm	30	20
43	15	39	19	M25 x 1.5mm	38	21
43	15	39	19	M25 x 1.5mm	38	21
49	16	46	26	M32 x 1.5mm	46	27
59	16	58	31	M40 x 1.5mm	59	35
59	16	72	41	M50 x 1.5mm	73	35

NOTE: Dimensions refer to an overall assembly

Straight (PG version) - Sealed fittings

Straight body Part No.	Cap nut	Sealing bush	Conduit size		Thread size
			NC	NW	
AB12-PG09	CN07	SRN07	10	8.5	PG09
AB12-PG11	CN07	SRN07	10	8.5	PG11
AB12-PG13	CN07	SRN07	10	8.5	PG13.5
AB12-PG09	CN09	SRN09	12	10	PG09
AB12-PG11	CN09	SRN09	12	10	PG11
AB12-PG13	CN09	SRN09	12	10	PG13.5
AB16-PG09	CN11	SRN11	16	13	PG09
AB16-PG11	CN11	SRN11	16	13	PG11
AB16-PG13	CN11	SRN11	16	13	PG13.5
AB20-PG16	CN16	SRN16	20	17	PG16
AB25-PG21	CN21	SRN21	25	22	PG21
AB25-PG21	CN28	SRN28	28	23	PG21
AB32-PG29	CN32	SRN32	32	29	PG29
AB40-PG36	CN36	SRN36	40	36	PG36
AB50-PG48	CN48	SRN48	50	48	PG48

NOTE: Order fitting bodies, cap nuts and sealing bushes separately
Part numbers for NPT and PF threads available on request

A	B	C	Min bore D	Thread E	A/F size F	G
32	10	23	10	PG09	22	17
32	10	23	14	PG11	22	17
32	10	23	16	PG13.5	22	17
32	10	23	10	PG09	22	17
32	10	23	14	PG11	22	17
32	10	26	16	PG13.5	27	17
32	10	26	10	PG09	27	17
32	10	26	14	PG11	27	17
32	10	26	16	PG13.5	27	17
35	11	31	18	PG16	30	20
40	12	39	23	PG21	38	21
40	12	39	23	PG21	38	21
45	12	46	31	PG29	46	27
55	12	58	38	PG36	59	35
55	12	72	50	PG48	73	35

NOTE: Dimensions refer to an overall assembly

