

Bushings, Nipples, Locknuts and Plugs

Made from flame-retardant, non-dripping thermoplastic, UL rated 105° C!

Knockout Plugs



Application

- To plug unused knockout openings in a box or enclosure

Features

- One-piece construction designed to snap in place
- High impact strength self-extinguishing non-dripping (per UL 94) thermoplastic construction

Standard Material

Thermoplastic rated for 105° C (221° F) application

Standard Finish

As molded

Range

.875" through 2.469"
Nominal Diameter

Knockout opening (1/2" through 2" trade size knockouts)

Wall thickness of box or enclosure

.095" max. up to 1" trade size

.140" max. through 2" trade size


Listings/Compliances

UL (UL File No. E13938)

CSA (LR589)

UL 514B

NFPA 70



105° C rated by UL. Made from flame retardant, non-dripping thermoplastic.



| CAT. NO. | SIZE | DIMENSION (IN.) | |
|----------|--------|-----------------|------|
| | | A | B |
| 1451 | 1/2" | 1.060 | .400 |
| 1452 | 3/4" | 1.300 | .400 |
| 1453 | 1" | 1.590 | .400 |
| 1454 | 1 1/4" | 1.860 | .450 |
| 1455 | 1 1/2" | 2.240 | .570 |
| 1456 | 2" | 2.740 | .570 |

Wall thickness of electrical box .095 max.

Meets Coast Guard Regulation CB293.

UL File No. E-13938 CSA File No. 4484

Eliminates need for separate capped bushing or steel penny and bushing!

Push-Penny® Plugs

Application

- To plug open end of conduit or connector in order to prevent ingress of trash, dirt or moisture during construction and remodeling

Features

- Wide range of applications; can be used with rigid metal conduit, intermediate metal conduit, electrical metallic tubing, all connectors and all bushings
- Designed to stand up to normal handling and is functionally unaffected by moisture
- Economically seal out grout and plaster from any fitting or raceway conforming to CSA dimensional tolerances
- Just push into place
- Pressure holds plug fast against internal surface of fitting or raceway
- Made of flexible plastic

Standard Material

Polyethylene

Standard Finish

As molded

Listings/Compliances

CSA (LR2884, LR4484)

UL 514B

CSA C22.2 No. 18

NFPA 70

NEMA FB1



| CAT. NO. | SIZE |
|----------|--------|
| 1470 | 1/2" |
| 1471 | 3/4" |
| 1472 | 1" |
| 1473 | 1 1/4" |
| 1474 | 1 1/2" |
| 1475 | 2" |
| 1476* | 2 1/2" |
| 1477* | 3" |
| 1478* | 3 1/2" |
| 1479* | 4" |

*Not CSA Certified.

CSA File No. 2884

UL not applicable.

Made to fit any bushing!

Steel Pennies

- Used under a bushing to seal end of conduit during construction
- Completely salvageable



| CAT. NO. | SIZE |
|----------|--------|
| 815-TB | 1/2" |
| 816 | 3/4" |
| 817 | 1" |
| 818 | 1 1/4" |
| 819 | 1 1/2" |
| 820 | 2" |

| CAT. NO. | SIZE |
|----------|--------|
| 821 | 2 1/2" |
| 822 | 3" |
| 824 | 3 1/2" |
| 823 | 4" |

UL not applicable.

CSA File No. 2884