


Product ordering and information


Narrow slot wiring duct

Designed to fit the spacing of high-density terminal blocks.


Narrow slot wiring duct — PVC

- Higher number of smaller fingers for more concise harnessing
- Non-slip cover does not slide easily and resists vibration
- Rounded edges protect hands and wires
- V-shaped slot lead-in enables easier and faster wire installation
- Restricted slot design makes sure that wires are held with or without the cover inserted
- Cover attaches flush with sidewall for finished look
- Dual score lines are designed to yield clean breakoffs at the base of the slot and the duct
- Finger design restricts wire from slipping along the edge; creates two or three levels of wire service (see page 34 for illustration)
- Integrated mounting holes — larger sizes include staggered holes for mounting flexibility (see page 30 for illustration)
- Constructed of flame-retardant PVC
- Lead-free construction






Front view with cover




Side view



Pattern for 3/4" & 1"

Pattern for 1 1/2"



Pattern for 2", 2 1/2", 3", 4" & 6"

For a complete listing of narrow slot dimensional details, see page 30.



| Cat. no. | Description (in.) | Size (W x H) | | Cover cat. no. | Duct std. ctn. qty. | Cover std. ctn. qty. | Length (ft.) |
|----------------|-----------------------------|--------------|---------------|----------------|---------------------|----------------------|--------------|
| | | in. | mm | | | | |
| TYD75X15NP[_]6 | 0.75 x 1.5 Narrow slot duct | 0.94 x 1.60 | 23.9 x 39.6 | TYD75CP[_]6 | 120 | 120 | 6 |
| TYD1X1NP[_]6 | 1 x 1 Narrow slot duct | 1.25 x 1.14 | 31.8 x 27.7 | TYD1CP[_]6 | 120 | 60 | 6 |
| TYD1X15NP[_]6 | 1 x 1.5 Narrow slot duct | 1.25 x 1.60 | 31.8 x 39.9 | | | | |
| TYD1X2NP[_]6 | 1 x 2 Narrow slot duct | 1.25 x 2.10 | 31.8 x 52.8 | | | | |
| TYD1X3NP[_]6 | 1 x 3 Narrow slot duct | 1.25 x 3.05 | 31.8 x 77.7 | | | | |
| TYD1X4NP[_]6 | 1 x 4 Narrow slot duct | 1.25 x 4.37 | 31.8 x 111.3 | | 60 | | |
| TYD15X1NP[_]6 | 1.5 x 1 Narrow slot duct | 1.75 x 1.14 | 44.5 x 27.7 | TYD15CP[_]6 | 120 | 60 | 6 |
| TYD15X15NP[_]6 | 1.5 x 1.5 Narrow slot duct | 1.75 x 1.60 | 44.5 x 39.9 | | | | |
| TYD15X2NP[_]6 | 1.5 x 2 Narrow slot duct | 1.75 x 2.10 | 44.5 x 52.8 | | | | |
| TYD15X3NP[_]6 | 1.5 x 3 Narrow slot duct | 1.75 x 3.05 | 44.5 x 77.7 | | | | |
| TYD15X4NP[_]6 | 1.5 x 4 Narrow slot duct | 1.75 x 4.37 | 44.5 x 111.3 | | 60 | | |
| TYD2X1NP[_]6 | 2 x 1 Narrow slot duct | 2.25 x 1.24 | 57.2 x 28.4 | TYD2CP[_]6 | 120 | 60 | 6 |
| TYD2X15NP[_]6 | 2 x 1.5 Narrow slot duct | 2.25 x 1.70 | 57.2 x 40.4 | | | | |
| TYD2X2NP[_]6 | 2 x 2 Narrow slot duct | 2.25 x 2.19 | 57.2 x 53.3 | | | | |
| TYD2X3NP[_]6 | 2 x 3 Narrow slot duct | 2.25 x 3.14 | 57.2 x 78.2 | | 60 | | |
| TYD2X4NP[_]6 | 2 x 4 Narrow slot duct | 2.25 x 4.46 | 57.2 x 111.8 | | | | |
| TYD2X5NP[_]6 | 2 x 5 Narrow slot duct | 2.25 x 5.15 | 57.2 x 129.3 | | | | |
| TYD25X2NP[_]6 | 2.5 x 2 Narrow slot duct | 2.75 x 2.19 | 69.9 x 53.6 | TYD25CP[_]6 | 120 | 60 | 6 |
| TYD25X3NP[_]6 | 2.5 x 3 Narrow slot duct | 2.75 x 3.14 | 69.9 x 78.2 | | 60 | | |
| TYD25X4NP[_]6 | 2.5 x 4 Narrow slot duct | 2.75 x 4.46 | 69.9 x 111.8 | | | | |
| TYD3X1NP[_]6 | 3 x 1 Narrow slot duct | 3.25 x 1.24 | 82.6 x 29.0 | TYD3CP[_]6 | 120 | 60 | 6 |
| TYD3X2NP[_]6 | 3 x 2 Narrow slot duct | 3.25 x 2.19 | 82.6 x 54.9 | | 60 | | |
| TYD3X3NP[_]6 | 3 x 3 Narrow slot duct | 3.25 x 3.14 | 82.6 x 79.8 | | | | |
| TYD3X4NP[_]6 | 3 x 4 Narrow slot duct | 3.25 x 4.46 | 82.6 x 113.5 | | | | |
| TYD3X5NP[_]6 | 3 x 5 Narrow slot duct | 3.25 x 5.15 | 82.6 x 130.6 | | | | |
| TYD4X2NP[_]6 | 4 x 2 Narrow slot duct | 4.25 x 2.19 | 108.0 x 55.1 | TYD4CP[_]6 | 60 | 30 | 6 |
| TYD4X3NP[_]6 | 4 x 3 Narrow slot duct | 4.25 x 3.14 | 108.0 x 80.0 | | | | |
| TYD4X4NP[_]6 | 4 x 4 Narrow slot duct | 4.25 x 4.46 | 108.0 x 113.8 | | 30 | | |
| TYD4X5NP[_]6 | 4 x 5 Narrow slot duct | 4.25 x 5.15 | 108.0 x 130.8 | | | | |

= space for color identifier:

- G = Gray
- W = White
- B = Black
- I = Intrinsic blue

- Standard lengths are 6 feet.
- + Catalog number must be completed by adding suffix G for gray, W for white, I for intrinsic blue, B for black.
- Example: TYD75X15NPG6 is a 0.75" x 1" wide slot gray duct.
- To order duct without mounting holes, add suffix NM to catalog number.
- Example: TYD75X15NPG6NM is a 0.75" x 1" wide slot gray duct with no mounting holes.
- To order adhesive-backed duct, add suffix A to catalog number.
- Example: TYD75X15NPG6A is a 0.75" x 1" wide slot gray duct with adhesive backing. Shelf life for adhesive is 1 year.
- PVC vinyl duct is CSA certified, UL recognized and CE compliant.