


Square Boxes and Accessories


Box Support Covers

Steel City® Box Support Covers combine a box-to-stud mounting bracket with a device cover in one, easy-to-use product. Designed for use with 4" square boxes, Steel City® Box Support Covers can be used with both steel and wood studs.

- Combines cover and bracket in one component
- Available in one- and two-device versions
- ½", ⅝" and ¾" raised covers
- Speeds installation time
- Needs no far side support
- Can be used with both steel and wood stud
- Can be used without a box as a low voltage device support
- UL and CSA Listed (UL File #E2969, CSA File #LR5043)



52CM13



52CMD17




CAT. NO.	RAISED (IN.)	# OF DEVICES	CU. IN. CAPACITY	STD. CTN.
52CM13	½	1	3.0	25
52CM14-5/8	⅝	1	4.0	25
52CM14	¾	1	5.0	25
52CMD17	½	2	6.3	25
52CMD18-5/8	⅝	2	7.3	25
52CMD18	¾	2	9.0	25


4" Square Surface Covers




RS 4




RS 1



RS 2




RS 3




RS 5

CAT. NO.	DEPTH (IN.)	CU. IN. CAPACITY	DIA. HOLE (IN.)	DESCRIPTION	STD. CTN.
RS 1	½	5.0	1 13/32	For one toggle switch and one single flush receptacle	50
RS 2*	½	5.0	—	For one toggle switch and one duplex flush receptacle	50
RS 3*	½	5.0	1 13/32	For one single and one duplex flush receptacle	50
RS 4	½	5.0	1 19/32	For one 4-wire twist-lock single receptacle	50
RS 5	½	5.0	—	For two toggle switches	50
RS 8*	½	5.0	—	For two duplex, flush receptacles	50
RS 9	½	5.0	—	For one toggle switch	50
RS 10	½	5.0	1 13/32	For two single, flush receptacles	50
RS 11	½	5.0	1 13/32	For one single, flush receptacle	50
RS 12*	½	5.0	—	For one duplex, flush receptacle	50
RS 13	½	5.0	2 5/32	For one 30 or 50 amp. dryer or range receptacle	50
RS 14	½	5.0	2 15/32	—	50
RS 15	½	5.0	1 ¼	For #3330-30A 250 V twist-lock receptacle	50
RS-16-CC	½	5.0	—	For one ground fault receptacle	25
RS-17-CC	½	5.0	—	For two ground fault receptacles	25
RS-18-CC	½	5.0	—	For one ground fault receptacle and one toggle switch	25
RS-19-CC*	½	5.0	—	For one ground fault receptacle and one duplex receptacle	25


Remove portion of G.F.I. receptacle ear to mount receptacle to cover. Screws captivated.




RS 8




RS 9




RS 10




RS 11




RS 12



RS 13




RS 14




RS 15




RS-16-CC



RS-17-CC



RS-18-CC



RS-19-CC