

# Ring terminals

Nylon-insulated large ring terminals (cont.)



| Cat. no. | Pkg. qty. | Wire range (AWG) | Max. ins. (in.) | Bolt hole (in.) | Rec. tool | Dimensions (in.) |      |      |      | Stock thick. (in.) |
|----------|-----------|------------------|-----------------|-----------------|-----------|------------------|------|------|------|--------------------|
|          |           |                  |                 |                 |           | A                | B    | C    | M    |                    |
| RG2-10   | 10        | 2                | 0.588           | #10             | TBM6S     | 2.15             | 0.69 | 0.40 | 1.83 | 0.05               |
| RG267    | 50        | 2                | 0.588           | #10             | TBM6S     | 2.15             | 0.69 | 0.40 | 1.83 | 0.05               |
| RG2-14   | 10        | 2                | 0.588           | ¼               | TBM6S     | 2.15             | 0.69 | 0.40 | 1.83 | 0.05               |
| RG717    | 50        | 2                | 0.588           | ¼               | TBM6S     | 2.15             | 0.69 | 0.40 | 1.83 | 0.05               |
| RG2-516  | 10        | 2                | 0.588           | ⅝               | TBM6S     | 2.15             | 0.69 | 0.40 | 1.83 | 0.05               |
| RG727    | 50        | 2                | 0.588           | ⅝               | TBM6S     | 2.15             | 0.69 | 0.40 | 1.83 | 0.05               |
| RG2-38   | 10        | 2                | 0.588           | ¾               | TBM6S     | 2.15             | 0.69 | 0.40 | 1.83 | 0.05               |
| RG737    | 50        | 2                | 0.588           | ¾               | TBM6S     | 2.15             | 0.69 | 0.40 | 1.83 | 0.05               |
| RG2-12   | 10        | 2                | 0.588           | ½               | TBM6S     | 2.35             | 0.80 | 0.49 | 1.93 | 0.05               |
| RG757    | 50        | 2                | 0.588           | ½               | TBM6S     | 2.35             | 0.80 | 0.49 | 1.93 | 0.05               |
| RG9711   | 50        | 2AN              | 0.453           | ¼               | TBM6S     | 2.07             | 0.69 | 0.40 | 1.74 | 0.05               |
| RG9731   | 50        | 2AN              | 0.453           | ⅜               | TBM6S     | 2.07             | 0.69 | 0.40 | 1.74 | 0.05               |
| RG9751   | 50        | 2AN              | 0.453           | ½               | TBM6S     | 2.26             | 0.80 | 0.49 | 1.84 | 0.05               |
| RH717    | 50        | 1/0              | 0.629           | ¼               | TBM6S     | 2.14             | 0.77 | 0.43 | 1.81 | 0.05               |
| RH727    | 50        | 1/0              | 0.629           | ⅝               | TBM6S     | 2.14             | 0.77 | 0.43 | 1.81 | 0.05               |
| RH737    | 50        | 1/0              | 0.629           | ¾               | TBM6S     | 2.14             | 0.77 | 0.43 | 1.81 | 0.05               |
| RH757    | 50        | 1/0              | 0.629           | ½               | TBM6S     | 2.34             | 0.77 | 0.54 | 1.90 | 0.05               |
| RH9711   | 50        | 1AN              | 0.500           | ¼               | TBM6S     | 2.14             | 0.77 | 0.44 | 1.81 | 0.05               |
| RH9731   | 50        | 1AN              | 0.500           | ⅜               | TBM6S     | 2.14             | 0.77 | 0.44 | 1.81 | 0.05               |
| RH9751   | 50        | 1AN              | 0.500           | ½               | TBM6S     | 2.34             | 0.77 | 0.54 | 1.90 | 0.05               |



| Cat. no. | Pkg. qty. | Wire range AWG | Max. ins. (in.) | Bolt hole (in.) | Rec. tool | Dimensions (in.) |      |      |      | Stock thick. (in.) |
|----------|-----------|----------------|-----------------|-----------------|-----------|------------------|------|------|------|--------------------|
|          |           |                |                 |                 |           | A                | B    | C    | M    |                    |
| RJ717    | 100       | 2/0            | 0.675           | ¼               | TBM6S     | 2.34             | 0.83 | 0.46 | 1.96 | 0.06               |
| RJ727    | 100       | 2/0            | 0.675           | ⅝               | TBM6S     | 2.34             | 0.83 | 0.46 | 1.96 | 0.06               |
| RJ737    | 100       | 2/0            | 0.675           | ¾               | TBM6S     | 2.34             | 0.83 | 0.46 | 1.96 | 0.06               |
| RJ757    | 100       | 2/0            | 0.675           | ½               | TBM6S     | 2.48             | 0.89 | 0.54 | 2.03 | 0.06               |
| RJ9711   | 50        | 1/0AN          | 0.550           | ¼               | TBM6S     | 2.35             | 0.83 | 0.46 | 1.97 | 0.06               |
| RJ9731   | 50        | 1/0AN          | 0.550           | ⅜               | TBM6S     | 2.35             | 0.83 | 0.46 | 1.97 | 0.06               |
| RJ9751   | 50        | 1/0AN          | 0.550           | ½               | TBM6S     | 2.49             | 0.89 | 0.55 | 2.04 | 0.06               |
| RK717    | 25        | 3/0            | 0.765           | ¼               | TBM6S     | 2.60             | 0.93 | 0.54 | 2.21 | 0.06               |
| RK727    | 25        | 3/0            | 0.765           | ⅝               | TBM6S     | 2.60             | 0.93 | 0.54 | 2.21 | 0.06               |
| RK737    | 25        | 3/0            | 0.765           | ¾               | TBM6S     | 2.60             | 0.93 | 0.54 | 2.21 | 0.06               |
| RK9731   | 100       | 2/0AN          | 0.610           | ⅜               | TBM6S     | 2.52             | 0.93 | 0.55 | 2.14 | 0.06               |
| RK9751   | 100       | 2/0AN          | 0.610           | ½               | TBM6S     | 2.60             | 0.93 | 0.55 | 2.15 | 0.06               |
| RL737    | 25        | 4/0            | 0.785           | ⅜               | TBM6S     | 2.83             | 1.04 | 0.57 | 2.35 | 0.07               |
| RL757    | 25        | 4/0            | 0.785           | ½               | TBM6S     | 2.83             | 1.04 | 0.57 | 2.35 | 0.07               |
| RL9731   | 25        | 3/0AN          | 0.680           | ⅜               | TBM6S     | 2.83             | 1.04 | 0.57 | 2.36 | 0.07               |
| RL9751   | 25        | 3/0AN          | 0.680           | ½               | TBM6S     | 2.83             | 1.04 | 0.57 | 2.36 | 0.07               |
| RM737    | 20        | 250            | 0.868           | ⅜               | TBM6S     | 3.00             | 1.13 | 0.65 | 2.51 | 0.07               |
| RM747    | 20        | 250            | 0.868           | ⅝               | TBM6S     | 3.00             | 1.13 | 0.65 | 2.51 | 0.07               |
| RM757    | 20        | 250            | 0.868           | ½               | TBM6S     | 3.00             | 1.13 | 0.65 | 2.51 | 0.07               |
| RM9731   | 20        | 4/0AN          | 0.750           | ⅜               | TBM6S     | 3.00             | 1.13 | 0.66 | 2.51 | 0.07               |
| RM9751   | 20        | 4/0AN          | 0.750           | ½               | TBM6S     | 3.00             | 1.13 | 0.66 | 2.51 | 0.07               |

