

Ring terminals

Nylon-insulated ring terminals



- Complete line of installing tools engineered to match tool with terminal
- First to gain military approval for pressure connections... many styles available for military applications
- Sta-Kon products exceed test specification requirements of military, UL and CSA
- Include extra metal sleeve to grip insulation
- Vinyl insulated and bare Sta-Kon terminals feature brazed seam wire barrels that can be crimped at any place on the barrel circumference
- Can be installed with crimping tools having a single indentor or double indentor (recommended for solid wire)
- Serrated barrel increases grip on wire
- Wire range identification on the tongue of each terminal
- Constructed of electrolytic copper for high conductivity



Cat. no.	Wire Pkg. range qty. (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
RZ22-2**	100 26-22	0.083	#2	ERG4006	0.57	0.14	0.13	0.49	0.02
RZ22-4**	100 26-22	0.083	#4	ERG4006	0.65	0.21	0.20	0.54	0.02
RZ22-6**	100 26-22	0.083	#6	ERG4006	0.65	0.21	0.20	0.54	0.02
RZ22-8**	100 26-22	0.083	#8	ERG4006	0.75	0.25	0.23	0.62	0.02
RZ22-10**	100 26-22	0.083	#10	ERG4006	0.75	0.25	0.23	0.62	0.02
RAX23*	1,000 26-24	0.125	#2	WT145A	0.66	0.14	0.14	0.59	0.02
RAX43*	1,000 26-24	0.125	#4	WT145A	0.74	0.20	0.19	0.64	0.02
RAX63*	1,000 26-24	0.125	#6	WT145A	0.84	0.25	0.22	0.72	0.02
RAX83*	1,000 26-24	0.125	#8	WT145A	0.84	0.25	0.22	0.72	0.02
RAX103*	1,000 26-24	0.125	#10	WT145A	0.84	0.25	0.24	0.72	0.02
RA18-4	100 22-16	0.136	#4	ERG4001	0.72	0.23	0.14	0.59	0.03
RA323	1,000 22-16	0.136	#4	ERG4001	0.72	0.23	0.14	0.59	0.03
RA333	1,000 22-16	0.136	#6	ERG4001	0.72	0.23	0.14	0.59	0.03
RA18-6	100 22-16	0.136	#6	ERG4001	0.86	0.26	0.25	0.71	0.03

* Not listed by UL or CSA

** CSA Certified only

Most standard bulk catalogue numbers can be put on mylar tape for reel feed applications (i.e. 12050 tool and application). Please add suffix M for mylar tape i.e. RA2573M.



Cat. no.	Wire Pkg. range qty. (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
RA853	1,000 22-16	0.136	#6	WT145A	0.86	0.26	0.25	0.71	0.03
RA18-8	100 22-16	0.136	#8	WT145A	0.89	0.26	0.25	0.71	0.03
RA833	1,000 22-16	0.136	#8	WT145A	0.86	0.26	0.25	0.71	0.03
RA863	1,000 22-16	0.136	#8	WT145A	0.89	0.26	0.25	0.71	0.03
RA18-10	100 22-16	0.136	#10	WT145A	0.89	0.31	0.25	0.71	0.03
RA873	1,000 22-16	0.136	#10	WT145A	0.89	0.31	0.25	0.71	0.03
RA18-14	100 22-16	0.136	¼	WT145A	1.10	0.46	0.31	0.84	0.03
RA713	1,000 22-16	0.136	¼	WT145A	1.10	0.46	0.31	0.84	0.03
RA18-516	100 22-16	0.136	⅜	WT145A	1.10	0.46	0.31	0.84	0.03
RA723	1,000 22-16	0.136	⅜	ERG4001	1.10	0.46	0.31	0.84	0.03
RA18-38	100 22-16	0.136	⅝	ERG4001	1.20	0.53	0.35	0.87	0.03
RA733	1,000 22-16	0.136	⅝	ERG4001	1.20	0.53	0.35	0.87	0.03
RA18-12	100 22-16	0.136	½	ERG4001	1.30	0.72	0.50	0.92	0.03
RA753	1,000 22-16	0.136	½	ERG4001	1.30	0.72	0.50	0.92	0.03

Diagram

