

6" Deluxe Universal Housings



IC Housing

Energy-efficient, Air-Loc® double wall housing can be covered with insulation. Includes Real Nail® 3 bar hangers.

IC2 6" IC new Construction Housing
IC2 G with pre-installed Air-Loc gasket
IC2 W with push-in electrical connectors
IC2 W G with push-in electrical connectors and pre-installed Air-Loc gasket

17 $\frac{3}{8}$ " L x 9 $\frac{5}{8}$ " W x 7 $\frac{1}{2}$ " H
 Ceiling cutout: 6 $\frac{7}{8}$ "



TC Housing

Requires 3" spacing from insulation. Includes Real Nail® 3 bar hangers (unless otherwise noted).

TC2 6" Non-IC New Construction Housing
TC2 S with smaller footprint bar hangers
 Real Nail® 2)
TC2 W with push-in electrical connectors

13 $\frac{1}{8}$ " L x 7 $\frac{1}{2}$ " W x 7 $\frac{1}{2}$ " H
 Ceiling cutout: 6 $\frac{7}{8}$ "



TC Remodel Housing

Requires 3" spacing from insulation. Installs from below ceiling.

TC2R Remodel Housing

13 $\frac{3}{4}$ " L x 7 $\frac{5}{16}$ " W x 5 $\frac{1}{4}$ " min H;
 7 $\frac{1}{4}$ " max H
 Ceiling cutout: 6 $\frac{3}{4}$ "

Note: In Canada when insulation is present, Type IC fixtures must be used.

6" Deluxe Universal Trims

Downlights



Tapered Baffle*

24 WWH White
 24 BBL Black
 24 BWH Black
 24 BABZ Black
 24 BSC Black
 75W PAR30L,
 65W BR30
 5 $\frac{1}{4}$ " Aperture



Straight Baffle

25 WWH White
 25 BWH Black
 25 BBL Black
 25 BSC Black
 IC: 85W BR40, 90W PAR38
 TC: 150W PAR38, 120W
 BR40
 5 $\frac{1}{4}$ " Aperture



PAR30 Deep Cone

257 BWH Black Alzak®
 257 CWH Clear Alzak®
 257 GWH Gold Alzak®
 257 HZWH Haze
 257 WHZWH Wheat Haze
 75W PAR30, 100W PAR38
 5 $\frac{1}{2}$ " Aperture



BR30 Open Frame

250 ABZ
 250 SC
 250 WH
 65W BR30
 4" Aperture



Pinhole with Baffle

23 BWH Black
 50W R/PAR20
 3 $\frac{3}{8}$ " Aperture



PAR30 Deep Baffle

254 WWH White
 254 BWH Black
 75W PAR30, 100W PAR38
 5 $\frac{1}{2}$ " Aperture



BR40/R40 Open Frame

251 WH
 IC: 100W BR40
 TC: 120W BR40, 250W R40
 Heat Lamp
 5 $\frac{1}{2}$ " Aperture

Trim Ring Finishes

ABZ Classic Aged Bronze
SC Satin Chrome
WH White
BL Black



Straight Cone

26 BWH Black Alzak®
 26 CWH Clear Alzak®
 26 GWH Gold Alzak®
 26 HZWH Haze
 26 PTSC Pewter Alzak®
 26 WWH Gloss White
 26 WHZWH Wheat Haze
 IC: 90W PAR38, 85W BR40
 TC: 150W PAR38,
 120W BR40
 5 $\frac{1}{4}$ " Aperture



Tapered Cone*

27 BWH Black Alzak®
 27 CWH Clear Alzak®
 27 GWH Gold Alzak®
 27 HZWH Haze
 27 PTSC Pewter Alzak®
 27 WWH Gloss White
 27 WHZABZ Wheat Haze
 27 WHZWH Wheat Haze
 75W PAR30L, 65W BR30
 5 $\frac{1}{8}$ " Aperture

Housing Accessories

Catalog Number	Description
ALG6	Energy Conserving Gasket for 6" New Construction Air-Loc® IC Housings
G2405	T-Bar Clips (Set of 4) for TC2 S
TR6 ABZ TR6 SC TR6 WH TR6 BL	6" Trim Ring compatible with 24, 25, 26, 27, 254 and 257 trims

* Trim may be used with TC2R housing adjusted in lowest (5-1/4") height position.