# 6" Deluxe Universal Line-Voltage Series, continued.

## 6" Deluxe Universal Trims

Trims listed below are for use with housings located on the preceding page 113.

#### **Downlights**



Ultra-Trim Baffle (Wet Location w/ Outdoor Lamps) Wet Location 28 WWH White 28 BWH Black IC: 75W A19, 100W PAR38, 75W PAR30/ 30L. 85W BR30. 120W BR40 TC: 100W A19, 150W A21, 150W PAR38, 75W PAR30/30L, 85W BR30, 120W BR40 5%" Aperture



**Ultra-Trim Cone** (Wet Location w/ AIR-LOC Outdoor Lamps) 29 CWH Deep - Clear 29 WWH Deep - White IC: 100W A19, 100W PAR38, 75W PAR30/30L, 85W BR30, 120W BR40 TC: 100W A19, 150W A21, 150W PAR38, 75W PAR30/30L, 85W BR30, 120W BR40 51/8" Aperture



A-Lamp Reflector 232 CWH Clear Alzak® 232 HZWH Haze 232 GWH Gold Alzak® 232 WWH Gloss White 232 WHZWH Wheat Haze IC2/TC2: 150W A21, 100W A19 IC2: 75W A19 (White Finish Only) TC2: 100W A19 (White Finish Only) 5%" Aperture



Economy A-Lamp **Reflector with Baffle** 230 CWWH Clear w/ White Baffle 230 CBWH Clear w/ Black Baffle 100W A19 51/2" Aperture



TC: 100W A19, 50W A21 51/8" Aperture

Shallow Baffle\* AIR-LOC 244S WWH White 244S BWH Black 75W PAR30/30L. 65W BR30 5¾" Aperture



AIR-LOC

**Shallow Cone** 247S CWH Clear Alzak® 247S GWH Gold Alzak® 247S BWH Black Alzak® 247S HZWH Haze 247S WHZWH Wheat Haze 75W PAR30/30L. 65W BR30 5<sup>3</sup>/<sub>4</sub>" Aperture

Adjustables



Low Voltage Cylinder Spotlight in Baffle\*\*\* 427 WWH White Cylinder with White Baffle 45° vertical adjustment, 358° rotation 50W MR16



R/PAR20 Regressed Eyeball\* 228 WH White 50W R/PAR20

R/PAR20 Regressed **Eyeball in Baffle\*** 248 WWH White 50W R/PAR20



PAR/BR30 Regressed Eveball\* 229 ABZ 229 BL 229 SC 229 WH 75W PAR30L, 65W BR30

PAR/BR30 Regressed Eveball in Baffle\* 249 WWH White 249 BWH Black 75W BB30



Cylinder Spotlight in Baffle\* 226 BWH Black Cylinder in Black Baffle 226 WWH White Cylinder in White Baffle 60W PAR16

### Wall Wash



Scoop 261 WWH White Baffle 261 BWH Black Baffle IC: 40W A19 TC: 75W A19

#### Lensed

PAR30 Adjustable

Low Voltage Pinhole

30° vertical adjustment,

**Tapered Baffle\*** 

264 WWH White

264 BWH Black

75W PAR30

5¾" Aperture

with Baffle\*

358° rotation

31/2" Aperture

IC: 35W MR16;

TC: 50W MR16

PAR30 Adjustable

267 BWH Black Alzak®

267 CWH Clear Alzak®

267 GWH Gold Alzak®

Gimbal Ring in Baffle

IC: 75W PAR38/Medium

224 WWH White 224 BWH Black

TC: 150W PAR38/

Medium Side Prong

Side Prong

5¾" Aperture

Tapered Cone\*

267 HZWH Haze

267 WHZWH

Wheat Haze

75W PAR30

5<sup>3</sup>/<sub>4</sub>" Aperture

424 BWH Black



Albalite 20 PW Shower/ Closet Light 20 WH IC: 40W A19 TC: 75W A19





240 PW Shower/ Closet Light 240 WH IC: 60W A19; TC: 100W A19

## 6" Standard Universals

Standard Universal downlights are offered with basic trim options but include all the installation and performance features Juno is known for.

### 6" Standard Universal Housings



#### IC Housing

Energy-efficient, Air-Loc® housing can be covered with insulation. Includes Real Nail® 3 bar hangers (unless otherwise stated).

IC226" IC New Construction HousingIC22 Gwith pre-installed Air-Loc gasketIC22 Swith smaller footprint bar hangers (Real Nail® 2)IC22 S Gwith smaller footprint bar hangers (Real Nail® 2) and pre-installed Air-Loc gasketIC22 Wwith push-in electrical connectorsIC22 W Gwith push-in electrical connectors and pre-installed Air-Loc gasket

131/8" L x 71/2" W x 71/8" H Ceiling cutout: 67/8"

## 6" Standard Universal Trims



IC Remodel Housing Energy-efficient, Air-Loc® housing can be covered with insulation. Installs from below ceiling with clips provided.

IC22R 6" IC Remodel Housing

13¾" L x 7½6" W x 7½" H Ceiling cutout: 6¾"

#### **BR/PAR Downlights** Ultra-Trim Baffle -**Tapered Cone BR30 Open Frame R/PAR20** Regressed Shallow Baffle AIR-LOC 27 BWH Black Alzak® 244S WWH White 250 ABZ **Fully Enclosed\*** Eveball 27 CWH Clear Alzak® 250 SC (Wet Location w/ 228 WH 244S BWH Black Wet Locatio Air-Loc 27 GWH Gold Alzak® 60W PAR30, 65W BR30, 250 WH Outdoor Lamps) 50W R/PAR20 27 HZWH Haze 28 WWH White 75W PAR30L 65W BR30 27 PTSC Pewter Alzak® 28 BWH Black **R/PAR20 Regressed** 5<sup>3</sup>/<sub>4</sub>" Aperture 4" Aperture 27 WWH Gloss White 60W A19, 65W BR30, Eyeball in Baffle 75W PAR30/30L, 27 WHZABZ Wheat Haze 248 WWH White 90W PAR38/BR40 27 WHZWH Wheat Haze 50W R/PAR20 50W PAR30, 65W BR30, 5<sup>7</sup>/<sub>8</sub>" Aperture 75W PAR30L Shallow Cone 5¾" Aperture Straight Baffle Adjustables 247S BWH Black Alzak® 25 WWH White 247S CWH Clear Alzak® 25 BBL Black 247S GWH Gold Alzak® 25 BABZ Black PAR/BR30 Regressed 247S HZWH Haze 25 BWH Black Eveball 247S WHZWH Wheat Haze 25 BSC Black 229 ABZ 75W PAR30L, 65W BR30, 50W PAR30, 65W BR30 **Tapered Baffle Cylinder Spotlight** 229 BL 75W PAR30 24 WWH White 5<sup>3</sup>/<sub>4</sub>" Aperture in Baffle 229 SC 5<sup>3</sup>/<sub>4</sub>" Aperture 24 BWH Black 226 WWH White 229 WH 24 BABZ Black Cvlinder 75W PAR30L. 24 BBL Black in White Baffle 65W BR30 226 BWH Black 24 BSC Black 75W PAR30L. Cylinder Ultra-Trim Cone -PAR/BR30 Regressed 50W PAR30, 65W BR30 in Black Baffle **Fully Enclosed\*** Eyeball in Baffle BR30 Regressed 60W PAR16 5¾" Aperture (Wet Location w/ 249 WWH White **Open Frame** Outdoor Lamps) 249 BWH Black 252 WH 29 CWH Clear Cone 75W PAR30L. 65W BR30 29 WWH White Cone 65W BR30 4" Aperture 60W A19, 65W BR30, 75W PAR30/30L, 90W PAR38/BR40 51/8" Aperture

## 6" Standard Universals with Floating Socket

Standard Universal downlights with floating sockets are optimized for the quickest possible attachment to enclosed and adjustable style trims.

## 6" Standard Universal Housings (Floating Socket)



Economy IC Housing

Energy-efficient, Air-Loc® housing with floating socket. Includes Real Nail® 3 bar hangers.

- IC23 6" IC No Plate New Construction Housing
- IC23 G with pre-installed Air-Loc gasket
- IC23 W with push-in electrical connectors

IC23 W G with push-in electrical connectors and pre-installed Air-Loc gasket

131/8" L x 71/2" W x 71/8" H Ceiling cutout: 67/8"

### 6" Standard Universal Trims

