

# 6" IC-Rated 900 and 1400 Lumen Super Slope Ceiling LED Downlights

6" new construction housings for use in super slope applications with 7/12 to 12/12 pitch (30° to 45°).

## 6" Super Slope New Construction



Dedicated 6" Super Slope Ceiling LED new construction housing with integral light engine and choice of dimmable drivers: 17.4W nominal dedicated 120 volt driver with forward phase and ELV dimming. Air-Loc fully sealed housing does not require separate gasket. IC housing designed for use in IC or non-IC construction.

18½" L x 9⅞" W x 7⅞" H  
Ceiling cutout: 8⅞" x 6⅞"

### Example: IC928LED G4 09LM 27K 90CRI 120 FRPC

Housing and trim can be ordered together or separately, but will always ship separately.

Series	Generation	Lumens	Color Temperature	CRI	Voltage/Driver*
<b>IC928LED</b> 6" LED Super Slope New Construction IC Housing	<b>G4</b> Generation 4	<b>09LM</b> 900 Nominal Lumens	<b>27K</b> 2700K	<b>90CRI</b> 90+ CRI	<b>120 FRPC</b> 120V Forward/Reverse Cut, 5% Dim.  * Consult factory for voltage/dimming options.
		<b>14LM</b> 1400 Nominal Lumens	<b>30K</b> 3000K		
			<b>35K</b> 3500K		
			<b>40K</b> 4000K		

## 6" Super Slope LED with WarmDim® Technology



Dedicated LED, Air-Loc® sealed slope ceiling new construction housing with our patented WarmDim® technology. The LED color temperature warms while dimming to emulate the dimming performance of traditional incandescent light source.

18½" L x 9⅞" W x 7⅞" H  
Ceiling cutout: 8⅞" x 6⅞"

### Example: IC928LED WD G4 09LM 30K 90CRI 120 FRPC

Housing and trim can be ordered together or separately, but will always ship separately.

Series	Dynamic Feature	Generation	Lumens	Color Temperature	CRI	Voltage/Driver
<b>IC928LED</b> 6" LED Super Slope Ceiling New Construction IC Housing	<b>WD</b> WarmDim®	<b>G4</b> Generation 4	<b>09LM</b> 900 Nominal Lumens  <b>14LM</b> 1400 Nominal Lumens	<b>30K</b> 3000K	<b>90CRI</b> 90+ CRI	<b>120 FRPC</b> 120V Forward/Reverse Phase Cut

## 6" Super Slope LED Trims

### Downlights



**Downlight Baffle**  
604 BWH Black  
604 BSC Black  
604 BABZ Black  
604 BBL Black  
604 WWH White



**Downlight Cone**  
602 CWH Clear Alzak®  
602 BWH Black Alzak®  
602 GWH Gold  
602 HZWH Haze  
602 HZSC Haze  
602 WWH White  
602 WHZWH Wheat Haze  
602 WHZABZ Wheat Haze



### Lensed



**Baffle, Regressed Frosted Dome Lens**  
6033 WWH White



### Trim Ring Finishes

**ABZ** Classic Aged Bronze  
**SC** Satin Chrome  
**WH** White  
**BL** Black

# 6" Incandescent Super Sloped Ceiling Downlights

Juno's patented Super Slope Ceiling Downlights are available in new construction or remodel versions for both insulated and non-insulated ceilings.

## 6" Super Slope Housings – 7/12 to 12/12 Pitch (30° to 45°)



### IC Housing

Energy-efficient, Air-Loc® double wall housing can be covered with insulation. Fits 2 x 8 construction.

**IC928** with Real Nail® 3 bar hangers  
**IC928 W** with push-in electrical connectors and Real Nail® 3 bar hangers

18½" L x 9½" W x 7⅝" H  
Ceiling opening: 6⅞" x 8⅞" oval

AIR-LOC



### TC Housing

Requires 3" spacing from insulation. For 2 x 8 or 2 x 10 construction.

**TC928** with Real Nail® 3 bar hangers

18½" L x 9½" W  
Adjustable fixture height: 7½" to 9⅞"  
Ceiling opening: 6⅞" x 8⅞" oval



### TC Remodel Housing

Requires 3" spacing from insulation. For 2 x 8 or 2 x 10 construction.

**TC928R** Remodel Housing

14" L x 7⅝" W  
Adjustable fixture height: 7⅝" to 9"  
Ceiling opening: 6⅞" x 8¼" oval

**Note:** In Canada when insulation is present, Type IC fixtures must be used.

## 6" Standard Super Slope Trims

### Downlights



#### Downlight Baffle

604 WWH White  
604 BWH Black  
604 BABZ Black  
604 BBL Black  
604 BSC Black  
IC: 90W PAR38  
TC: 150W PAR38  
For superior baffling, use 75W PAR30



#### Reflector Cone

602 BWH Black Alzak®  
602 CWH Clear Alzak®  
602 GWH Gold Alzak®  
602 HZSC Haze  
602 HZWH Haze  
602 WWH White  
602 WHZABZ Wheat Haze  
602 WHZWH Wheat Haze  
IC: 75W PAR30, 90W PAR38, 85W BR30  
TC: 75W PAR30, 150W PAR38, 85W BR30

### Adjustables



#### Cylinder Spotlight in Baffle

606 WWH White  
606 BWH Black  
60W PAR16  
45° vertical adjustment, 358° rotation

### Lensed



#### Lensed Shower Trim

Flat Diffuser  
603 WWH White  
603 BWH Black  
IC: 50W PAR30  
TC: 75W A19, 75W PAR30



### Accessories

Catalog Number	Description
<b>ALG928</b>	Energy Conserving Gasket for Air-Loc® IC928 Housings

### Trim Ring Finishes

<b>ABZ</b> Classic Aged Bronze	<b>WH</b> White
<b>SC</b> Satin Chrome	<b>BL</b> Black