

# 6" Incandescent Sloped Ceiling Downlights

Patented Juno Slope Ceiling Downlights direct light straight down, providing proper light distribution from a sloped surface.

## 6" Standard Slope Housings – 2/12 to 6/12 Pitch (9° to 27°)



**AIR-LOC**

### IC Housing

Energy-efficient, Air-Loc® double wall housing can be covered with insulation. Fits 2 x 8 construction.

**IC926** with Real Nail® 3 bar hangers

**IC926 W** with push-in electrical connectors and Real Nail® 3 bar hangers

16 1/8" L x 9 1/8" W x 7 7/8" H  
Ceiling opening: 7 1/2" x 6 1/16" oval



### TC Housing

Requires 3" spacing from insulation. For 2 x 8 or 2 x 10 construction.

**TC926** with Real Nail® 3 bar hangers

16 1/8" L x 9 1/8" W  
Adjustable fixture height: 7 1/2" to 9"  
Ceiling opening: 7 1/2" x 6 1/16" oval



### TC Remodel Housing

Requires 3" spacing from insulation. For 2 x 8 or 2 x 10 construction.

**TC926R** Remodel Housing

14" L x 6 7/8" W  
Adjustable fixture height: 7 1/2" to 9"  
Ceiling opening: 6 1/2" x 6 7/8" oval

**Note:** In Canada when insulation is present, Type IC fixtures must be used.

## 6" Standard Slope Trims

### Downlights



#### Downlight Baffle\*

**614 WWH** White  
**614 BWH** Black  
**614 BABZ** Black  
**614 BBL** Black  
**614 BSC** Black  
IC: 90W PAR38  
TC: 150W PAR38



#### Reflector Cone

**612 BWH** Black Alzak®  
**612 CWH** Clear Alzak®  
**612 GWH** Gold Alzak®  
**612 HZSC** Haze  
**612 HZWH** Haze  
**612 WWH** White  
**612 WHZABZ** Wheat Haze  
**612 WHZWH** Wheat Haze  
IC: 75W PAR30, 90W PAR38, 65W BR30  
TC: 75W PAR30, 150W PAR38, 85W BR30

### Adjustables



#### Cylinder Spotlight in Baffle

**616 WWH** White  
**616 BWH** Black  
60W PAR16  
45° vertical adjustment, 358° rotation



#### Low Voltage Cylinder Spotlight in Baffle

**617 WWH** White  
45° vertical adjustment, 358° rotation  
IC: 35W MR16  
TC: 50W MR16  
Supplied with magnetic transformer. Use dimmers specifically designed for low voltage magnetic transformers.



#### Eyeball in Baffle

**619 WWH** White  
**619 BWH** Black  
35° vertical adjustment, 358° rotation  
IC/TC: 85W BR30

### Lensed



#### Lensed Shower Trim

Flat Diffuser  
**610 WWH** White  
**610 BWH** Black  
IC: 50W PAR30  
TC: 75W A19, 75W PAR30



### Accessories

Catalog Number	Description
<b>ALG926</b>	Energy Conserving Gasket for Air-Loc® IC926 Housings

### Trim Ring Finishes

<b>ABZ</b> Classic Aged Bronze	<b>WH</b> White
<b>SC</b> Satin Chrome	<b>BL</b> Black

\* Patent pending one piece design eliminates the unsightly seam on the long side of the baffle.

U.S. Patent No. 4,729,08. Canadian Patent No. 1264158.