

4" MR16 Universal Trims

The trims shown here may be used with any 4" MR16 Universal housing on page 98.

Downlight Trims



Deep Cone

442 BWH Black Alzak® Cone
442 CWH Clear Alzak® Cone
442 GWH Gold Alzak® Cone
442 HZWH Haze
442 WHZWH Wheat
Haze Cone
50W MR16
3 3/8" Aperture



Pinhole with Baffle

443 BWH Pinhole,
White with Black Baffle
IC/TC44: 50W MR16;
TC47: 75W MR16
1 1/4" Aperture

Adjustables



Baffle - Downlight/ Adjustable

444 WWH White Baffle
444 BWH Black Baffle
444 BABZ Black Baffle
444 BSC Black Baffle,
444 BBL Black Baffle
30° vertical adjustment
IC/TC44: 50W MR16;
TC47: 75W MR16
3 3/8" Aperture



Cone - Downlight/Adjustable

447 BWH Black Alzak®
447 CWH Clear Alzak®
447 GWH Gold Alzak®
447 HZWH Haze
447 PTSC Pewter
447 WHZABZ Wheat Haze
447 WHZWH Wheat Haze
35° vertical adjustment
IC/TC44: 50W MR16;
TC47: 75W MR16
3 3/8" Aperture



Flush Gimbal Ring

440 ABZ
440 BL
440 SC
440 WH
40° vertical adjustment
50W MR16
Uses 2" light control
lenses-consult factory.



Adjustable Slot Aperture

445 WH
45° vertical adjustment
IC/TC44: 50W MR16;
TC47: 75W MR16
1 1/2" x 2 1/2" Slot Aperture



Eyeball w/Black Baffle

448 WH
35° vertical adjustment
IC/TC44: 50W MR16;
TC47: 75W MR16



Aiming Elbow

449 ABZ
449 BL
449 SC
449 WH
75° vertical adjustment
50W MR16

Lensed



Downlight/Adjustable Shower Trim

441 WABZ
441 WSC
441 WWH
35° vertical adjustment
50W MR16



Wall Wash



Adjustable Scoop


446 WH
45° vertical adjustment
IC/TC44: 50W MR16;
TC47: 75W MR16

Squares



Square Pinhole Trim

443SQ WH White
IC/TC44: 50W MR16




Downlight Adjustable Trim

447SQ HZWH Haze
447SQ BWH Black
447SQ WHZWH Wheat Haze
IC/TC44: 50W MR16
35° Vertical Adjustment



Square Flush Gimbal Trim

440SQ WH
440SQ BL
IC/TC44: 50W MR16
35° Vertical Adjustment



Downlight Adjustable Square Lensed Trim

441SQ WWH White,
35° Vertical Adjustment



Trim Ring Finishes

ABZ Classic Aged Bronze
SC Satin Chrome
WH White
BL Black

Housing Accessories

Catalog Number	Description
4TSA	Torsion Spring Adapter use in TC44, IC44N and TC47
SMPLT4	4" Smash Plate for TC44R
G2405	T-Bar Clips (Set of 4) for TC44 S, IC44N S

For light control accessories, see page 101.

4" Line Voltage Trims

The trims shown here may be used with 4" R/PAR20 Universal housing on page 104.

Downlights



Pinhole with Integral Shield
13 WH
 IC1: 30W R20, 35W PAR20
 IC1P/TC: 50W PAR/R20
 IC1P: 40W K19
 2" Aperture



Baffle
14 WWH White
14 BBL Black
14 BWH Black
14 BABZ Black
14 BSC Black
 IC1: 50W PAR20
 (Requires T599
 Socket Extender),
 50W R20
 IC1P/TC1/TC1R: 50W
 PAR/R20
 3 3/8" Aperture



PAR20/R20 Cone
17 BWH Black Alzak®
17 CWH Clear Alzak®
17 GWH Gold Alzak®
17 HZWH Haze
17 PTSC Pewter Alzak®
17 WWH Gloss White
17 WHZABZ Wheat Haze
17 WHZWH Wheat Haze
 IC1/IC1P/TC1/TC1R:
 50W PAR/R20
 IC1P: 60W K19
 3 3/8" Aperture

Adjustables



Gimbal Ring
10 ABZ
10 BL
10 SC
10 WH
 IC1P/TC: 50W PAR20;
 75W ES20 (120V GU10)
 Adjustment: PAR20=25°,
 ES20=35°



Mini Eyeball PAR16
18 SC
18 WH
 40W R16
 60W PAR16
 Adjustment: 35° vertical



Mini Eyeball
19 WH
 IC-25W R14; TC-40W R14,
 40W R16
 (Intermediate screw base lamp)
 Adjustment: 35° vertical



Flush Gimbal Ring
440 WH
440 BL
440 SC
440 ABZ
 35W MR16/ES16 GU10 base
 (Requires GU10WHIP)



Slot
445 WH
 50W MR16/ES16 120V GU10
 base (Not used with IC1).
 (Requires GU10WHIP)
 Adjustment: 40° vertical



Eyeball with Black Baffle
448 WH
448 SC
 35W MR16/ES16 GU10 base
 (Requires GU10WHIP)

Wall Wash



Scoop
16 WH
 IC-25W R14; TC-40W R14,
 40W R16
 (Intermediate screw base
 lamp) Adjustment: 50° vertical

Scoop
446W
 50W MR16/ES16 120V GU10
 base (Not used with IC1)
 (Requires GU10WHIP)
 Adjustment: 40° vertical

Lensed




Frosted Lens with Clear Center
12 WABZ
12 WSC
12 WWH
 IC1: 30W R20,
 50W PAR20 with 1"
 socket extender #T599
 IC1P/TC: 50W PAR/R20
 IC1P: 40W K19



Drop Opal
11 WH
 IC1: 30W R20,
 35W PAR20
 IC1P: 30W R20,
 50W PAR20, 40W K19
 TC: 50W PAR/R20

Squares



Downlight
17SQ HZWH Haze
17SQ WWH White
17SQ BWH Black
17SQ WHZWH Wheat Haze
 50W PAR20 (Requires T599
 socket extender), 39W
 PAR20, 30W R20



Flush Gimbal
440SQ WH
440SQ BL
 35W MR16 120V
 (Requires GU10WHIP).
 Adjustment: 35° vertical



Pinhole
13SQ WH White
 50W PAR20 (Requires T599
 socket extender), 35W PAR20,
 30W E20



Frosted Lens with Clear Center
12SQ WWH White
 50W PAR20
 (Requires T599 socket
 extender), 30W R20



Trim Ring Finishes

ABZ Classic Aged Bronze
SC Satin Chrome
WH White
BL Black