

**Intended Use**

Use in high mounting heights that require high efficiencies, horizontal illumination and premium glare control. Ideal for general manufacturing areas and warehouse aisles.

**Features**

- Die-cast aluminum housing
- Integral splice box mounting flange ensures structural integrity
- A17: premium spun aluminum anodized 17" reflector

- PA22 or PA22L: high-performance UV-stabilized prismatic acrylic refractor (available lensed or open)
- Electronic HID ballasts are 100% factory-tested
- 3/4" threaded hub for suspended mounting with rigid conduit (other mounting options available)

**Listings**

UL and cUL Listed for damp locations, 40°C ambient.

# RHMC A17

# RHMC PA22



With lens option

**ORDERING INFORMATION**

Specifications subject to change.

**Example:** RHMC 210MP A17 208 HEB CR

Series	Wattage <sup>2</sup>	Reflector	Voltage	Ballast
RHMC <sup>1</sup>	Protected metal halide	A17 Open aluminum	208	HEB
	210MP 210W <sup>2,3</sup>	PA22 Open acrylic	240	
	315MP 315W <sup>2</sup>	PA22L Lensed (tempered glass acrylic)	277	
			TVOLT	

  

Options					Finish	
SF	Single fuse (277) <sup>4</sup>	LOCS	Loop, 5' white cord, RELOC <sup>®</sup> OCS <sup>4,7</sup>	GL17	Tempered glass lens <sup>9</sup>	(blank) Textured dark gray with aluminum accents
DF	Double fuse (208, 240) <sup>4</sup>	HOCS	Hook, 5' white cord, RELOC OCS <sup>4,7</sup>	GL17WG	Tempered glass lens with wireguard <sup>9</sup>	DNA Gloss natural aluminum with aluminum accents
EC	Emergency circuit <sup>4,5,6</sup>	LOCU	Loop, 5' white cord, RELOC OCU <sup>4,7</sup>	DIM	Dimming access terminal	DBLB Textured black with aluminum accents
QRS	Quartz restrike system <sup>4,5,6</sup>	HOCU	Hook, 5' white cord, RELOC OCU <sup>4,7</sup>	CSA	Listed and labeled to comply with Canadian Standards	DWH Gloss white
LCPP	Loop, cord, plug requires TPH, PPH <sup>4</sup>	W/Lamp	210W or 315W lamp <sup>8</sup>	NOM	NOM Certified (consult factory)	CR Corrosion-resistant finish
LC3P	Loop, 3' cord, 15A NEMA <sup>®</sup> twist-lock plug <sup>4</sup>	Q150DC	QRS lamp for 210W <sup>8</sup>			
HC3P	Hook, 3' cord, 15A NEMA twist-lock plug <sup>4</sup>	Q175DC	QRS lamp for 315W <sup>8</sup>			

**ADDITIONAL INFORMATION**

For additional product information, visit [www.lithonia.com](http://www.lithonia.com).

**ACCESSORIES****ORDER SEPARATELY**

HKF	Fixture hook female
LPF	Fixture loop female
SCK	60" safety chain kit
WGA17	Wireguard <sup>9</sup>
HKM	Fixture hook male
HKMG	Grommated fixture hook male
LPM	Fixture loop male
LPMG	Grommated fixture loop male
TPH	Through-wire power hook <sup>10</sup>
PPH	Pendant power hook <sup>10</sup>
DCY	Cylinder shade
DSQ	Square shade
DHX	Hexagonal shade

**Notes**

- Lamp not included.
- These wattages comply with California Title 20.
- Dimming over 25% of operational time not recommended by lamp/ballast manufacturer.
- Must specify voltage.
- Quartz lamp max wattage is 150 for 210M. QRS max wattage is 250 for 315M.
- Option is not field-installable. Must be factory-installed.
- May be ordered with 10', 15' and 20' cords. For black cord, specify BK (i.e.: HOCSEBK).
- Will ship as separate line item.
- When ordering GL17 option, wireguard must be factory-installed on glass.
- Must use with LCPP.

Certain airborne contaminants can diminish integrity of acrylic and polycarbonate. Refer to the Acrylic & Polycarbonate Environmental Compatibility tables on pages 1116-1117 for suitable uses.