

Aluminum Rigid Conduit (ARC)

Click brand for more product info ↓

Aluminum Rigid Conduit (ARC)

[Allied Tube & Conduit](#)
[Calconduit](#)



Features:

- Manufactured of 6063 alloy in temper designation T-1
- Corrosion resistant Aluminum
- Light weight
- Easy installation
- Low maintenance
- Complete line of elbows and couplings
- Available in sizes 1/2 (16) – 6 (155)
- Color-coded end caps keep threads clean and sharp and help provide trade size recognition

Certifications & Compliances:

- Listed to UL Safety Standard 6A
- Certified to Canadian Standards Association Safety Standard CSA C22.2 No.45.2
- Manufactured in accordance with ANSI C80.5



Part Number	Trade Size		Outside Diameter*		Nominal Wall Thickness		Approximate Weight Per 100 ft (30.5m)		Quantity In Master Bundle	
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)	(ft)	(m)
732035	1/2	16	0.84	21.34	0.104	2.64	28	12.7	2500	762.5
732036	3/4	21	1.05	26.67	0.107	2.72	37	17	2500	762.5
732302	1	27	1.315	33.4	0.126	3.2	55	24.7	2000	610
732303	1 1/4	35	1.66	42.16	0.133	3.38	72	32.5	1000	304.8
732304	1 1/2	41	1.9	48.26	0.138	3.51	89	40.2	1000	304.8
732305	2	53	2.375	60.33	0.146	3.71	119	53.8	450	137.2
732306	2 1/2	63	2.875	73.03	0.193	4.9	188	85	300	91.5
732307	3	78	3.5	88.9	0.205	5.21	246	111.7	200	61
732308	3 1/2	91	4	101.6	0.215	5.46	296	134.1	200	61
732309	4	103	4.5	114.3	0.225	5.72	350	158.9	200	61
732310	5	129	5.563	141.3	0.245	6.22	479	217.2	80	23.4
732311	6	155	6.625	168.28	0.266	6.76	635	287.8	60	18.3

All dimensions are for informational purposes only *Tolerances +/- 5%