

EMT Conduit

E-Z Pull® EMT

Click brand for more
product info
[Allied Tube & Conduit](#)
[Calconduit](#)



Features:

- Manufactured from high grade mild strip steel for exceptional durability and long-lasting life
- Hot galvanized steel using patented inline Flo-Coat® process for long lasting exterior protection
- E-Z Pull® interior coating provides a smooth surface for faster wire pulling
- Excellent mechanical protection for conductors
- Ductility for faster and easier bending
- Very effective in reducing effects of EMI

Certifications & Compliances:

- Allied UL certified to Safety Standard 797
- Manufactured in accordance with ANSI C80.3
- Columbia-MBF CSA certified to Standard CSA C22.2 No. 83.1
- Listed in category FJMX
- Master bundles conform to NEMA Standard RN 2
- Recognized as an equipment grounding conductor by NEC Section 250-118 and by CEC Section 10



Part Number	Trade Size		Outside Diameter*		Nominal Wall Thickness		Approximate Weight Per 100 ft (30.5m)		Galvanized Master Bundle Quantity	
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)	(ft)	(m)
898302	1/2	16	0.706	17.93	0.042	1.07	30	13.6	7000	2135
898303	3/4	21	0.922	23.42	0.049	1.24	46	20.9	5000	1525
898304	1	27	1.163	29.54	0.057	1.45	67	30.4	3000	915
101576	1 1/4	35	1.51	38.35	0.065	1.65	101	45.8	2000	610
101584	1 1/2	41	1.74	44.2	0.065	1.65	116	52.6	1500	457.5
101592	2	53	2.197	55.8	0.065	1.65	148	67.1	1200	366
101600	2 1/2	63	2.875	73.03	0.072	1.83	216	98	610	186.1
101618	3	78	3.5	88.9	0.072	1.83	263	119.3	510	155.6
101782	3 1/2	91	4	101.6	0.083	2.11	349	158.3	370	112.9
101790	4	103	4.5	114.3	0.083	2.11	393	178.3	300	91.5

* Outside diameter tolerances:

+/- .005 (in) (.13mm) for trade sizes 1/2" (16mm) through 2" (53mm)

+/- .010 (in) (.25mm) for trade sizes 2 1/2" (63mm)

+/- .015 (in) (.38mm) for trade size 3" (78mm)

+/- .020 (in) (.51mm) for trade sizes 3 1/2" (91mm) and 4" (103mm)

NOTE: Length = 10 (ft) (3.05m) with a tolerance of +/- .25 (in) (6.35 mm)