


Armored Cable/Flexible Metallic Conduit Fittings

Straight Squeeze-Type Connectors — Malleable Iron

CAT. NO.	CONDUIT SIZE (IN.)	UNIT QTY.	STD. CTN.
XC-400	⅜ (½ KO)	50	100
XC-401	½	25	100
XC-402	¾	25	100
XC-403	1	25	100
XC-404	1¼	5	10
XC-405	1½	10	10
XC-406	2	10	10
XC-407	2½	5	5
XC-408	3	5	5

UL File No. E-1383 ⅜"-¾".

UL File No. E-23018 1"-3".



Straight Squeeze-Type Connectors — Insulated Malleable Iron

CAT. NO.	CONDUIT SIZE (IN.)	UNIT QTY.	STD. CTN.
XC-901	½	25	100
XC-902	¾	25	100
XC-903	1	25	100
XC-904	1¼	5	10
XC-905	1½	10	10
XC-906	2	10	10
XC-907	2½	5	5
XC-908	3	5	5

UL File No. E-1383 ½"-¾".

UL File No. E-23018 1"-3".



Clamp Straight Set, 90° and Duplex Connectors


90° Angle Squeeze-Type Connectors — Steel or Malleable Iron/Zinc Plated

CAT. NO.	CONDUIT SIZE (IN.)	UNIT QTY.	STD. CTN.
XC-490	⅜ (½ KO)	50	100
XC-491	½	25	100
XC-492	¾	25	50
XC-493	1	25	25
XC-494	1¼	10	10
XC-495	1½	10	10
XC-496	2	5	5
XC-497	2½	1	1
XC-498	3	1	1

UL File No. E-1383 ⅜" & ¾".

UL File No. E-23018 1"-3".

⅜"-¾" — Steel.



XC-490

Note: For die-cast armored cable/flexible metallic conduit fittings and combination fittings, see Steel City® Die-Cast Conduit Fittings, pages E-550-E-552.

Straight Squeeze-Type Connectors — Die-Cast Zinc

CAT. NO.	FIG.	SIZE (IN.)	DIMENSIONS (IN.)			STD. CTN.
			A (MIN.)	A (MAX.)	B	
XC-269	1	⅜ (½ KO)	.45	.60	.96	500
XC-270	1	½	.74	.92	1.43	250
XC-272	1	¾	.88	1.10	1.59	250
XC-273	2	1	1.10	1.35	1.60	100
XC-274	2	1¼	1.48	1.65	1.91	100
XC-275	2	1½	1.68	2.00	2.12	50
XC-276	3	2	2.12	2.47	2.54	40
XC-277	3	2½	2.71	3.08	2.88	10
XC-278	3	3	3.15	3.60	3.88	5
XC-278A	3	3½	3.20	4.03	5.04	1
XC-2710	3	4	3.15	4.25	5.04	—

UL File No. E-1383 ⅜" & ¾".

UL File No. E-23018 1"-3".

⅜"-¾" — Steel.

