

SAW BLADES

Reciprocating Saw Blades



Metal

Wood With
Nails

Plastic

Demolition

Drywall

Cement
Board

Cast Iron

Block

Stainless
SteelStructural
Steel

GREENLEE EXTREME Ti-Metal® Blades





























- High performance Titanium (Ti) coating + Improved Bi-Metal blades = GREENLEE EXTREME Ti-Metal®
- The super-hard titanium coating helps dissipate heat and resists wear on the cutting teeth
- Extreme Ti-Metal® blades stay sharp, cut faster, and last longer... even in the most demanding applications

GREENLEE EXTREME Blades

- Heavy-duty blades for heavy metal applications
- Designed specifically for extreme metal cutting in structural steel I-Beam and angle iron
- Thicker, wider blades cut straighter and resist bending during high-load cuts

GREENLEE Bi-Metal Blades

- Greenlee blades feature improved bi-metal material with added cobalt for increased toughness, durability and blade life
- Precision cutting teeth are designed to stay sharp and cut fast, saving valuable time on the job
- Available in a variety of blade types for cutting wood, nail embedded wood, metal, and other demanding construction materials

	CAT. NO.	LENGTH X WIDTH X THICKNESS INCH / MM	MATERIAL	QTY/ PK	TEETH PER INCH	SPEED AND QUALITY OF CUT
EXTREME Ti-METAL						
NOTE: Minimum blade length = Material width + 3"						
	353-624G	6 x 3/4 x .035 / 152 x 19 x .9	 BEST for sheet metal (1/8" and less).	5	24T	 FASTER, ROUGHER
	353-818G	8 x 3/4 x .035 / 203 x 19 x .9	 BEST for thin metal (1/16" - 3/16").	5	18T	
	353-618G	6 x 3/4 x .035 / 152 x 19 x .9	 BEST for thin metal (1/16" - 3/16").	5	18T	
	353-614G	6 x 3/4 x .035 / 152 x 19 x .9	 BEST for medium metal (3/32" - 3/8").	5	14T	
	353-610G	6 x 3/4 x .035 / 152 x 19 x .9	   BEST for general purpose.	5	10T	
	353-810G	8 x 3/4 x .050 / 203 x 19 x 1.3	   BEST for general purpose.	5	10T	
	353-656G	6 x 3/4 x .050 / 152 x 19 x 1.3	 BEST for clean wood and wood with nails. (plunge cutting)	5	6T	
EXTREME						
NOTE: Minimum blade length = Material width + 3"						
	353-6118	6 x 1 x .042 / 152 x 25 x 1.1	 BEST for structural steel (up to 1/4").	5	18T	 SLOWER, SMOOTHER
	353-9118	9 x 1 x .042 / 229 x 25 x 1.1	 BEST for structural steel (up to 1/4").	5	18T	
	353-6114	6 x 1 x .042 / 152 x 25 x 1.1	 BEST for structural steel (up to 3/8").	5	14T	
	353-9114	9 x 1 x .042 / 229 x 25 x 1.1	 BEST for structural steel (up to 3/8").	5	14T	



Metal



Wood With
Nails



Plastic



Demolition



Drywall



Cement
Board



Cast Iron



Block














































Stainless
Steel



Structural
Steel

Reciprocating Saw Blades

	CAT. NO.	LENGTH X WIDTH X THICKNESS INCH / MM	MATERIAL	QTY/ PK	TEETH PER INCH	SPEED AND QUALITY OF CUT
BI-METAL						
NOTE: Minimum blade length = Material width + 3"						
	353-624	6 x 3/4 x .035 / 152 x 19 x .9	 BETTER for sheet metal (1/8" and less).	5	24T	SLOWER, SMOOTHER ↑
	353-818	8 x 3/4 x .035 / 203 x 19 x .9	 BETTER for thin metal (1/16" - 3/16").	5	18T	
	353-618	6 x 3/4 x .035 / 152 x 19 x .9	 BETTER for thin metal (1/16" - 3/16").	5	18T	
	353-814	8 x 3/4 x .050 / 203 x 19 x 1.3	 BETTER for medium metal (3/32" - 3/8").	5	14T	
	353-614	6 x 3/4 x .035 / 152 x 19 x .9	 BETTER for medium metal (3/32" - 3/8").	5	14T	
	353-414	4 x 3/4 x .035 / 102 x 19 x .9	 BETTER for medium metal (3/32" - 3/8").	5	14T	
	353-804	8 x 3/4 x .050 / 203 x 19 x 1.3	 BETTER for thick metal (1/8" - 1/2").	5	10/14T	
	353-835	8 x 3/4 x .035 / 203 x 19 x .9	 BETTER for general purpose.	5	10/14T	
	353-635	6 x 3/4 x .035 / 152 x 19 x .9	 BETTER for general purpose.	5	10/14T	
	353-110	12 x 3/4 x .050 / 305 x 19 x 1.3	 BETTER for general purpose.	5	10/14T	
	353-810	8 x 3/4 x .050 / 203 x 19 x 1.3	 BETTER for general purpose.	5	10T	↓ FASTER, ROUGHER
	353-610	6 x 3/4 x .035 / 152 x 19 x .9	 BETTER for general purpose.	5	10T	
	353-123	6 x 3/4 x .035 / 152 x 19 x .9	 BETTER for general purpose.	5	8/18T	
	353-969	9 x 7/8 x .063 / 229 x 22 x 1.6	 BEST for demolition projects.	5	8/10T	
	353-646	6 x 3/4 x .050 / 152 x 19 x 1.3	 BETTER for clean wood and wood with nails.	5	6T	
	353-656	6 x 3/4 x .050 / 153 x 19 x 1.3	 BETTER for clean wood and wood with nails. (plunge cutting)	5	6T	
	353-956	9 x 3/4 x .050 / 229 x 19 x 1.3	 BETTER for clean wood and wood with nails. (plunge cutting)	5	6T	
	353-156	12 x 3/4 x .050 / 305 x 19 x 1.3	 BETTER for clean wood and wood with nails. (plunge cutting)	5	6T	
	353-636	6 x 3/4 x .050 / 152 x 19 x 1.3	 BETTER for drywall and plaster.	5	6T	
SPECIALTY						
NOTE: Minimum blade length = Material width + 3"						
	353-800RDG	8 x 3/4 x .039 / 203 x 19 x 1	  BEST for cast iron pipe, block & brick and other abrasives such as tile.	1	Diamond Grit	SLOWER, SMOOTHER ↑
	353-618RS	6 x 3/4 x .039 / 152 x 19 x 1	 BEST for stainless steel (1/16" - 3/16"). Carbide teeth	1	18T	
	353-656RCT	6 x 3/4 x .050 / 152 x 19 x 1.3	 BEST for cement board, fiber board, and plaster. Carbide tipped	1	6T	