

ME-S Male Enlargers

Explosionproof, Dust-Ignitionproof

NEC/CEC:
 Class I, Division 1 and 2, Groups A, B, C, D
 Class II, Division 1 and 2, Groups E, F, G
 Class III

Applications

- Enlarges a threaded hub in an enclosure or fitting. Example: A 3/4" conduit may connect to a 1/2" female hub by using an ME-323S. See illustration below.

Features

- Knurled female hub.
- Tapered threaded hubs (NPT) for Rigid Conduit and IMC.

Standard Materials

- Turned steel


Standard Finishes

- Zinc electroplated

NEC/CEC Certifications and Compliances

- UL Standards: ANSI/UL 514B and 886
- UL Listed: E-34997
- CSA Standard: C22.2 No. 30
- CSA Certified: 009795
- Suitable for wet locations
- NEC Articles 500-503 and 505



	Trade Size (Inches)	Dimensions in Millimeters (Inches)			Weight per 100 kg (lb)	Catalog Number
		A	B	C		
Male Enlargers — Turned Steel						
	3/4F x 1/2M	14.20 (0.56)	19.80 (0.78)	35.10 (1.38)	7.26 (16.00)	ME-323S
	1F x 3/4M	12.70 (0.50)	23.90 (0.94)	44.50 (1.75)	1.80 (26.00)	ME-324S
	1-1/4F x 1M	14.20 (0.56)	26.90 (1.06)	57.20 (2.25)	21.32 (47.00)	ME-325S

