







## Flush Round Single or Multi-Service Non-Metallic Floor Boxes, for Use In Concrete Floors

	
<b>Min. Depth of Pour</b>	3.00" (76.2)
<b>Cubic Inch (cm<sup>3</sup>) Capacity</b>	100 cu. in. (1638.7 cm <sup>3</sup> ) prior to cutting level to floor (19.5 cu. in. (313.2 cm <sup>3</sup> ) per inch of depth).
<b>Dimensions – A</b>	6.00" (152.4)
<b>Dimensions – B</b>	7.08" (179.8)
<b>Dimensions – C</b>	6.69" (169.9)
<b>Dimensions – D</b>	5.38" (136.5)
<b>Hubs</b>	(2) 1" and (2) ¾" Conduit Hubs
<b>Concrete Cover Included</b>	✓
<b>Closure/Reducer Plugs</b>	(2) 1" plugs close off 1" hubs or reduce 1" to ¾" (2) ¾" plugs close off ¾" hubs or reduce ¾" to ½"

Note: UL File Number E92074. CSA File Number LR18416.

Description	Catalog Number
<b>Adapter</b> Required for all applications.	 <b>PFBA1A</b>
<b>Low Voltage Divider</b> Required for use with catalog number <b>PFB1</b> when used in multi-service applications. Accepts Hubbell standard duplex receptacles or 15A Twist-Lock® duplex receptacles (HBL4700 series).	 <b>PFBT1A</b>
<b>"Y" Adapter</b> ¾ in. "Y" adapter to feed parallel runs of ¾ in. conduit.	 <b>PFBYA1</b>
Pre-pour PVC stand increases <b>PFB1</b> box height 2.5 in. to 4.0 in. within the concrete pour.	 <b>PFBSTAND</b>

## Flush Round Covers and Flanges†

**Multi-Service Cover and Flange Assemblies**  
Includes floor box cover with duplex flaps, (2) ½ in. dia. low voltage feed through holes and matching carpet flange. 6.25 in. Diameter

**SF39253A**



Brass

**PFBCBRA**



Brown  
Non-Metallic

**PFBCBLA**



Black  
Non-Metallic

**PFBCGYA**



Gray  
Non-Metallic

**PFBCIA**



Ivory  
Non-Metallic

## Metal Carpet Flange

Use with single service covers for carpet applications. 6.25 in. Diameter

**S3082**



Brass

**SA3082**



Brushed  
Aluminum

## Adapter Ring

Use with single service covers for tile applications.

**S5016**



Brass

**SA5016**



Aluminum

## Multi-Service Replacement Covers


Material	Metallic	Color	Non-metallic
Solid Brass	<b>BRS2RCA</b>	Black Brown Gray Ivory	<b>PFBRCBLA</b> <b>PFBRCBRA</b> <b>PFBRCGYA</b> <b>PFBRCIA</b>



## Single Service Covers†

Brass  
Aluminum  
3.88 in. Dia.

**S3925**  
**SA3925**



Duplex  
Flap

**S3725**  
**SA3725**



Duplex  
Screw

**S2525**  
**SA2525**



2 1/8" x ¾"  
Combination

**S2725**  
**SA2725**



2 1/8" x 1"  
Combination

**S2925**  
**SA2925**



2 1/8" Single  
Receptacle

**S3525**  
—



2 3/8" Single  
Receptacle

**S3325**  
—



2 1/8" Single  
Receptacle  
(Terrazzo Floor)

**S3913**  
**SA3913**



Blank

## One Piece Brass Cover and Carpet Flange†


Brass  
Aluminum  
6.25 in. Dia.

**SF3925\***  
**SFA3925\***



Duplex  
Flap

**SFB3926\*\***  
**SFA3926**



Style Line®  
Decorator  
Opening

**SF2525\***  
—



2 1/8" x ¾"  
Combination

**SF2725\***  
—



2 1/8" x 1"  
Combination

**SF2925\***  
—



2 1/8" Single  
Receptacle

## Furniture Feed Plate

Unpainted plate with  
1 in. threaded opening.

**PFBP1**



Steel

\*Note: Adapter ring S5016 is required for mounting SF series covers onto PFBA1A.

\*\*Note: brass plated aluminum

†COVER LOAD RATING; Metallic covers and flanges 2,000 lbs. with 2x safety factor, Non-metallic covers and flanges 300 lbs. Load applied through a 3 in. (76) mandrel at the center of the cover.