

# Single Pole Devices and Temporary Power

## Construction Site Lighting

Hubbell's outdoor approved construction site lighting line includes both heavy duty metal halide lights and light strings for working in rugged environments. The metal halide fixtures feature extremely strong and compact heads with bulbs rated to last 10,000 hours. All frames are powder-coated yellow for safety and are constructed of a durable 1.25 inch, 12 gauge steel tube.

We have light strings for all applications in a variety of models as well as a choice of metal or plastic guards. Light sockets are spaced 10 feet apart and all sockets, plugs, and connectors are molded for added durability. In addition, the highly impact-resistant material makes for easy transportation and storage when not in use. Bulbs can be incandescent, fluorescent or LED. Consider choosing LED lighting for a durable bulb that saves energy, provides instant illumination and are rated to last 50,000 hours.



HBLMH400

### Metal Halide and LED Lights

| Description                                  | Rating   | Watts | Lumen Output | Cord Length | Catalog Number     |
|----------------------------------------------|----------|-------|--------------|-------------|--------------------|
| High bay metal halide light with wire guard. | 15A 125V | 400   | 29,000       | 3 ft.       | <b>HBLMH400</b>    |
| High bay LED light with wire guard.          | 15A 125V | 120   | 14,000       | 5 ft.       | <b>HBLLEDHB120</b> |
|                                              | 15A 125V | 100   | 12,000       | 5 ft.       | <b>HBLLEDHB100</b> |
|                                              | 15A 125V | 60    | 7,200        | 5 ft.       | <b>HBLLEDHB60</b>  |



HBLLEDHB120

### LED Stringer Lights

| Description                                                    | No. of Fixtures | Rating   | Cord Type  | Lumen Output | Cord Length | Catalog Number       |
|----------------------------------------------------------------|-----------------|----------|------------|--------------|-------------|----------------------|
| 90 LEDs per fixture, light string with magnetic base included. | 1               | 15A 125V | #18/2 SJTW | 450*         | 20 ft.      | <b>HBL182S20LED</b>  |
| 90 LEDs per fixture, light string.                             | 5               | 15A 125V | #18/2 SJTW | 450*         | 50 ft.      | <b>HBL182S50LED</b>  |
|                                                                | 10              | 15A 125V | #18/2 SJTW | 450*         | 100 ft.     | <b>HBL182S100LED</b> |
| 60 LEDs per fixture, light string with magnetic base included. | 1               | 15A 125V | #18/2 SJTW | 1,100*       | 20 ft.      | <b>HBL182S20LEDH</b> |
|                                                                | 5               | 15A 125V | #18/2 SJTW | 1,100*       | 50 ft.      | <b>HBL182S50LEDH</b> |
| Magnetic clip bracket for LED light string.                    |                 |          |            |              |             | <b>HBLSTMC</b>       |

Note: \*Lumens per fixture.



HBL182S50LEDH

### A Type (Edison) Twist-Lock® and Straight Blade Light Strings

| Description                                                     | Max Watts** | Rating   | Cord Type  | Fixtures | Cord Length | Catalog Number       |
|-----------------------------------------------------------------|-------------|----------|------------|----------|-------------|----------------------|
| Twist-Lock® light string; plastic guards.                       | 150         | 20A 125V | #12/3 STJW | 10       | 100 ft.     | <b>HBL123SJ100PT</b> |
| Straight Blade light string; plastic guards.                    | 150         | 15A 125V | #14/2 STJW | 10       | 100 ft.     | <b>HBL142SJ100PS</b> |
|                                                                 | 150         | 15A 125V | #14/3 STJW | 10       | 100 ft.     | <b>HBL143SJ100PS</b> |
|                                                                 | 150         | 15A 125V | #12/3 STW  | 10       | 100 ft.     | <b>HBL123S100PS</b>  |
|                                                                 | 150         | 15A 125V | #12/3 STJW | 10       | 100 ft.     | <b>HBL123SJ100PS</b> |
| Straight Blade light string; metal guards.                      | 150         | 15A 125V | #12/3 STW  | 10       | 100 ft.     | <b>HBL123S100MS</b>  |
| Straight Blade light string; plastic guards.                    | 150         | 15A 125V | #12/3 STW  | 5        | 50 ft.      | <b>HBL123S50PS</b>   |
| Straight Blade light string; metal guards.                      | 150         | 15A 125V | #12/3 STW  | 5        | 50 ft.      | <b>HBL123S50MS</b>   |
| Replacement plastic guard for temporary light strings.          |             |          |            |          |             | <b>HBLSTPG</b>       |
| Replacement heavy duty metal guard for temporary light strings. |             |          |            |          |             | <b>HBLSTMG</b>       |

Note: \*\*Max watts per fixture. **HBL143SJ100PS** light strings are rated for 1875 Watts total. The total wattage must be considered when daisy chaining lights strings to each other.



HBL143SJ100PS



HBLSTMC



HBLSTMG



HBLSTPG