

Wire-Nut® Wire Connectors

The American Classic Since 1928

- Fixed square spring for a secure hold
- Refined range to handle all common applications
- Positive grip shell that is perfect to twist-on with fingers
- Excellent for fine stranded wire applications
- UL Listed to 105°C (221°F)



Model	Color	Wire Combination Range	Wire Combination Range (mm)	Quantity	Part No.
71B®	Gray	300V 22 to 16 AWG Min. 2 #22 Str. – Max. 2 #16	300V .34mm ² to 1.5mm ² Min. 2-.34mm ² Max. 3-1.5mm ²	Box of 100	30-071
				Carton of 1,000	30-171
				Barrel of 25,000	30-271
72B®	Blue	300V 22 to 14 AWG Min. 2 #22 – Max. 3 #16	300V .34mm ² to 2.5mm ² Min. 2-.34mm ² Max. 3-1.5mm ²	Box of 100	30-072
				Carton of 1,000	30-172
				Barrel of 10,000	30-272
				Barrel of 85,000	30-872
73B®	Orange	600V* 22 to 14 AWG Min. 1 #18 w/1 #20 Max. 2 #14	600V* .34mm ² to 2.5mm ² Min. 1-.75mm ² w/1-.50mm ² Max. 4-1.5mm ² w/1-.50mm ²	Box of 100	30-073
				Jar of 300	30-073J
				Carton of 1,000	30-173
				Bag of 500	30-273
				Barrel of 10,000	30-673
74B®	Yellow	600V* 18 to 12 AWG Min. 2 #18 Max. 4 #14 w/1 #18	600V* .75mm ² to 4.0mm ² Min. 2-.75mm ² Max. 4-2.5mm ² w/1-.75mm ²	Barrel of 50,000	30-873
				Box of 100	30-074
				Jar of 175	30-074J
				Bag of 500	30-274
				Carton of 1,000	30-174
76B®	Red	600V* 18 to 6 AWG Min. 2 #14 Max. 4 #12	600V* .75mm ² to 16.0mm ² Min. 2-2.5mm ² Max. 2-4.0mm ²	Barrel of 5,000	30-674
				Barrel of 35,000	30-874
				Box of 100	30-076
				Jar of 150	30-076J
				Bag of 250	30-276
				Carton of 1,000	30-176
				Barrel of 15,000	30-876

*1,000V maximum in fixtures and signs

High-Temp Wire-Nut® Wire Connectors

All of the same features as the Wire-Nut® Wire Connector, plus:

- Black, thermoplastic shell designed to withstand extreme heat build-up found in high-wattage light fixtures and signs
- UL Listed to 150°C (302°F)



Model	Color	Wire Combination Range	Wire Combination Range (mm)	Quantity	Part No.
71B®	Black	300V 22 to 16 AWG Min. 2 #22 Str. – Max. 2 #16	300V .34mm ² to 1.5mm ² Min. 2-.34mm ² – Max. 2-1.5mm ²	Box of 100	30-3627
				Carton of 1,000	30-151
				Barrel of 25,000	30-251
72B®	Black	300V 22 to 14 AWG Min. 2 #22 – Max. 3 #16	300V .34mm ² to 2.5mm ² Min. 2-.34mm ² – Max. 3-1.5mm ²	Box of 100	30-3628
				Carton of 1,000	30-152
				Barrel of 10,000	30-252
73B®	Black	600V* 22 to 14 AWG Min. 1 #18 w/1 #20 - Max. 2 #14	600V* .34mm ² to 2.5mm ² Min. 1-.75mm ² – Max. 4-1.5mm ² w/1-.50mm ²	Box of 100	30-3629
				Carton of 1,000	30-153
				Barrel of 10,000	30-253
59B™	Black	600V* 22 to 12 AWG Min. 2 #20 – Max. 3 #14	600V* .34mm ² to 4.0mm ² Min. 2-.5mm ² – Max. 3-2.5mm ²	Barrel of 50,000	30-803
				Box of 100	30-059
				Carton of 1,000	30-159
				Barrel of 5,000	30-259

*1,000V maximum in fixtures and signs