

## Stripmaster® & Stripmaster® Lite Wire Strippers

- One-step stripping enhances productivity
- Precision-ground, knife-type blades provide clean, accurate stripping
- Sturdy die-cast zinc frame provides long-term durability
- Stripmaster® Lite designed for smaller hands – 3/4 the size of the standard Stripmaster®
- 90-day warranty



### Stripmaster® Wire Strippers and Knife-Type Blades

| Specifications – Stripping Holes Offered |   |                                     |    |    |    |    |    |    |    |    |    |    | Replacement<br>Blades (Pair)<br>Part No. | Replacement<br>Frame<br>Part No. | Tool w/<br>Blades<br>Part No. |
|------------------------------------------|---|-------------------------------------|----|----|----|----|----|----|----|----|----|----|------------------------------------------|----------------------------------|-------------------------------|
| Wire Size AWG                            |   |                                     |    |    |    |    |    |    |    |    |    |    |                                          |                                  |                               |
| 6                                        | 8 | 10                                  | 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26 | 28 | 30 |                                          |                                  |                               |
|                                          | • | •                                   | •  |    |    |    |    |    |    |    |    |    | L-4419                                   | L-5620                           | 45-090                        |
|                                          |   | •                                   | •  | •  | •  | •  |    |    |    |    |    |    | L-4420                                   |                                  | 45-091                        |
|                                          |   | •                                   | •  | •  | •  | •  | •  | •  |    |    |    |    | L-4421                                   |                                  | 45-092 or<br>45-292*          |
|                                          |   |                                     |    | •  | •  | •  | •  | •  |    |    |    |    | L-4422                                   |                                  | 45-093                        |
| •                                        | • | This tool has custom step grippers. |    |    |    |    |    |    |    |    |    |    | L-4453                                   | —                                | 45-096                        |
|                                          |   |                                     |    |    | •  | •  | •  | •  | •  | •  |    |    | L-4994                                   | L-5620                           | 45-097                        |
|                                          |   |                                     |    |    |    |    | •  | •  | •  | •  | •  | •  | L-5361                                   |                                  | 45-098                        |
|                                          | • | •                                   |    |    | •  | •  |    |    |    |    |    |    | L-8763                                   |                                  | 45-099                        |

\* Blister Card

### Stripmaster® Lite Wire Strippers and Knife-Type Blades

| Specifications – Stripping Holes Offered |    |    |    |                                           |    |    |    |    |    | Replacement<br>Blades (Pair)<br>Part No. | Replacement<br>Frame<br>Part No. | Tool w/<br>Blades<br>Part No. |
|------------------------------------------|----|----|----|-------------------------------------------|----|----|----|----|----|------------------------------------------|----------------------------------|-------------------------------|
| Wire Size AWG                            |    |    |    |                                           |    |    |    |    |    |                                          |                                  |                               |
| 12                                       | 14 | 16 | 18 | 20                                        | 22 | 24 | 26 | 28 | 30 |                                          |                                  |                               |
|                                          |    | •  | •  | •                                         | •  |    |    |    |    | LB-1001                                  | LB-1421                          | 45-671                        |
|                                          |    |    |    |                                           |    | •  | •  | •  | •  | LB-1002                                  |                                  | 45-672                        |
| •                                        | •  | •  | •  | All stranded wire                         |    |    |    |    |    | LB-1003                                  |                                  | 45-673                        |
| •                                        | •  | •  | •  | 12 & 14 Solid Wire, 16 & 18 Stranded Wire |    |    |    |    |    | LB-1004                                  |                                  | 45-674                        |

### Stripmaster® Wire Strippers and Knife-Type Blades for Metric Wire

| Specifications – Stripping Holes Offered |     |      |      |      |     |      |   |     |     |   |   |   |    | Replacement<br>Blades (Pair)<br>Part No. | Replacement<br>Frame<br>Part No. | Tool w/<br>Blades<br>Part No. |
|------------------------------------------|-----|------|------|------|-----|------|---|-----|-----|---|---|---|----|------------------------------------------|----------------------------------|-------------------------------|
| Wire Size mm²                            |     |      |      |      |     |      |   |     |     |   |   |   |    |                                          |                                  |                               |
| 0.05                                     | 0.1 | 0.15 | 0.22 | 0.34 | 0.5 | 0.75 | 1 | 1.5 | 2.5 | 4 | 6 | 8 | 10 |                                          |                                  |                               |
|                                          |     |      |      |      |     |      |   |     |     |   |   | • | •  | L-4419M                                  | LA-2358                          | 45-090-341                    |
|                                          |     |      |      |      |     | •    | • | •   | •   | • | • |   |    | L-4421M                                  |                                  | 45-092-341 or<br>45-292-341*  |
| •                                        | •   | •    | •    | •    | •   |      |   |     |     |   |   |   |    | L-5361M                                  |                                  | 45-098-341                    |

\*Blister Card

| Description                                         | Blade Gap<br>vertical<br>height | Blade Only<br>Part No. | Frame &<br>Blade<br>Part No. |
|-----------------------------------------------------|---------------------------------|------------------------|------------------------------|
| Custom Steel frame only                             | —                               | —                      | LB-1091                      |
| Flat blade for 26 AWG (.40mm dia.) multi-conductor  | .022 in.                        | LB-1151                | 45-890                       |
| Flat blade for 24 AWG (.00mm dia.) multi-conductor  | .030 in.                        | LB-1152                | 45-891                       |
| Flat blade for 22 AWG (.64mm dia.) multi-conductor  | .038 in.                        | LB-1153                | 45-892                       |
| Flat blade for 20 AWG (.00mm dia.) multi-conductor  | .050 in.                        | LB-1154                | 45-893                       |
| Flat blade for 18 AWG (1.02mm dia.) multi-conductor | .060 in.                        | LB-1155                | 45-894                       |
| Flat blade for 16 AWG (1.29mm dia.) multi-conductor | .075 in.                        | LB-1156                | 45-895                       |