

## General Purpose Vinyl Electrical Tape

- For primary insulation up to 600V
- Cold and weather resistant from 32°F-176°F (0°C-80°C)
- Good elasticity up to 200% for ease of application
- Flame retardant

| Color  | Size               | Qty. | Part No.            |
|--------|--------------------|------|---------------------|
| Black  | 3/4" x .007" x 60' | 10   | <b>46-1700</b>      |
| Blue   | 3/4" x .007" x 66' |      | <b>46-1700C-BLU</b> |
| Brown  |                    |      | <b>46-1700C-BRN</b> |
| Gray   |                    |      | <b>46-1700C-GRY</b> |
| Green  |                    |      | <b>46-1700C-GRN</b> |
| Orange |                    |      | <b>46-1700C-ORN</b> |
| Red    |                    |      | <b>46-1700C-RED</b> |
| Violet |                    |      | <b>46-1700C-VIO</b> |
| White  |                    |      | <b>46-1700C-WHT</b> |
| Yellow |                    |      | <b>46-1700C-YLW</b> |

**NEW**



TOOLS & SUPPLIES

## Linerless Rubber Tape

- Primary insulation up to 69kV
- Linerless ethylene rubber
- Excellently conforms to complex shapes
- Moisture, corrosion, and chemical resistant
- High thermal conductivity allowing heat to dissipate from joint
- Overload temperature: 266°F
- Elongation: 890%



| Dimensions           | Part No.              |
|----------------------|-----------------------|
| 3/4" x 0.03" x 30'   | <b>46-130C-3/4x30</b> |
| 1" x 0.03" x 30'     | <b>46-130C-1x30</b>   |
| 1-1/2" x 0.03" x 30' | <b>46-130C-1.5x30</b> |
| 2" x 0.03" x 30'     | <b>46-130C-2x30</b>   |

## Mastic Pads

- Primary insulation up to 1kV
- Superior adhesion and dielectric strength
- Sealing and insulating for buried, submerged or overhead electrical connections
- Resistant to UV rays and impermeable to ozone, water, soil, dirt and corrosive chemicals
- Overload temperature: 266°F



| Dimensions          | Qty. | Part No.             |
|---------------------|------|----------------------|
| 6-1/2" x 0.13" x 4" | 10   | <b>46-2200-6.5x4</b> |

## Rubber Mastic Tape

- Primary insulation up to 2kV
- Insulating and moisture sealing splices and terminations
- Moisture, corrosion and chemical resistant
- Suitable for direct burial and overhead applications
- Overload Temperature: 266°F
- Elongation: 890%



| Dimensions        | Part No.            |
|-------------------|---------------------|
| 1" x 0.065" x 10' | <b>46-2228-1x10</b> |

## Corrosion Protection Tape

- Protects pipe, joints, conduit and couplings in overhead or direct burial applications
- Highly resistant to sun, water, oil, acids, alkalies, and corrosive chemicals
- Bacteria and fungus resistant
- Pressure sensitive
- Thickness: 10 mil



| Dimensions        | Part No.               |
|-------------------|------------------------|
| 2" x 0.01" x 100' | <b>46-50-UNPRINT-2</b> |