

Multi-Purpose Cable Ties


- General purpose cable tie for building and cable management
- UL recognized and Plenum rated



Size		Thickness x Width	Color	Tensile Strength (lbs.)	UL/CSA Type	Plenum Approval	Qty.	Part No.				
Miniature	4 in.	.042 in. x .095 in.	Natural	18	21	AH-2	100	B-4-18-9-C				
			UL Black				100	B-4-18-0-C				
Intermediate	6 in.	.049 in. x .140 in.	Natural	40	100		B-6-40-9-C					
			Natural		1,000		B-6-40-9-M					
			UV Black		100		B-6-40-0-C					
			8 in.		.053 in. x .180 in.		Burgundy	50	100	B-8-50-35-C		
	11 in.	100	B-11-50-35-C									
Standard	8 in.	.053 in. x .180 in.	Natural	50	21S		AH-2	100	B-8-50-9-C			
			Natural					1,000	B-8-50-9-M			
			UV Black					100	B-8-50-0-C			
			UV Black					1,000	B-8-50-0-M			
	11 in.		Natural					100	B-11-50-9-C			
			Natural					500	B-11-50-9-D			
			UV Black					100	B-11-50-0-C			
			UV Black					500	B-11-50-0-D			
	14 in.		Natural					100	B-14-50-9-C			
			Natural					500	B-14-50-9-D			
			UV Black					100	B-14-50-0-C			
			UV Black					500	B-14-50-0-D			
		Heavy-Duty	14 in.	.076 in. x .300 in.				Natural	120	21	100	B-14-120-9-C
			UV Black					50			B-14-120-0-L	
24 in.	Natural		175		50			B-24-175-9-L				
UV Black	50				B-24-175-0-L							
36 in.	Natural	50			B-36-175-9-L							
48 in.	Natural	50			B-48-175-9-L							
Mounting Ties	8 in.	.052 in. x .177 in.	Natural	50	21	AH-2		100	B-8-50MT-9-C			
		UV Black	100					B-8-50MT-0-C				
	14 in.	.053 in. x .178 in.	Natural					100	B-14-50MT-9-C			
Mounting Pads	3/4 in. x 3/4 in.	.189 Max. Tie Width	Natural	9	11	—		100	BMP-750-9-C			
	1 in. x 1 in.	.142 in. Max Tie Width	Natural	11	11	—		100	BMP-1000-9-C			

Mounting Head, Natural & UV Black Cable Ties

- Secures and positions wire bundles, cables, hoses, etc. to panels or other surfaces with one fastener to reduce time and cost
- Allows bundling before and after mounting



Description	Length	Width	Thickness	Max. Bundle	Tensile Strength	Screw Size	UL/CSA Type	Plenum Approval	Qty./ Bag	Part No.
Natural Nylon	6.0 in.	.138 in.	.045 in.	1/16 - 1-1/4 in.	40 lbs.	No. 8	11	AH-2	100	IT1_5IMH-C
UV Black Nylon	152mm	3.50mm	1.14mm						100	IT1_5IMH-C0
Natural Nylon	8.1 in.	.177 in.	.052 in.	1/16 - 1-3/4 in.	50 lbs.	No. 10			100	IT2SMH-C
Natural Nylon									206mm	4.49mm
UV Black Nylon									100	IT2SMH-C0
Natural Nylon	11.8 in.	.177 in.	.053 in.	1/16 - 3 in.	50 lbs.	No. 10			100	IT3SMH-C
UV Black Nylon	363mm	4.49mm	1.34mm						100	IT3SMH-C0
Natural Nylon	14.5 in.	.177 in.	.053 in.	1/16 - 4 in.	50 lbs.	No. 10			100	IT4SMH-C
Natural Nylon	15.7 in.	.248 in.	.075 in.	3/16 - 4-1/16 in.	120 lbs.	1/4 in.	21		100	IT4LHMH-C
UV Black Nylon	398mm	7.56mm	1.90mm						100	IT4LHMH-C0

UL Listed Nylon 6/6 cable ties are suitable for use in air handling spaces in accordance with Section 300-22(C) & (D) of the National Electrical Code.

