45

## 3M<sup>™</sup> Outdoor Masking and Stucco Tape 5959

3M<sup>TM</sup> Outdoor Masking and Stucco Tape 5959 is built strong, holds strong, and removes clean, even up to 90 days after application. Its unique, polyethylene backing, laid over a dense cloth scrim, is strong enough to pull through spatter from stucco, Exterior Insulation and Finishing Systems (EIFS) and other heavy coatings.

Adhesive Material
Backing Material
Tape Type
Maximum Operating

Temperature

Rubber

Polyethylene over cloth scrim/rubber

Special Use 200°F (93°C)



Order No.	UPC	Color	Length	Width	Thickness	Elongation	Breaking Strength	Adhesion to Steel	Rolls per Case
5959	051115-25491	Red	41.1 m	48 mm	12.0 mil	21%	35 lbs/in (613 N/100 mm)	53 oz/in (58 N/100 mm)	12 individually wrapped rolls

## 3M<sup>™</sup> Heavy Duty Duct Tape 3939

3M<sup>™</sup> Heavy Duty Duct Tape 3939 is composed of waterproof polyethylene film over cloth scrim backing with a rubber adhesive used for demanding duct tape applications.

Adhesive Material
Backing Material

Rubber

Backing Material Polyethylene Film Over Cloth Scrim

Tape Type

**Agency Approval** 

Special Use

Maximum Operating Temperature 200°F (93°C)

RoHS 2011/65/EU Flame Spread Index

Yes 0 30

Smoke Development Index

(II)

Tested in accordance with UL723/ASTM E84



Order No.	UPC	Color	Length	Width	Thickness	Elongation	Breaking Strength	Adhesion to Steel	Rolls per Case
3939-24MMX54.8M	021200-85561	Silver	54.8 m	24 mm	9 mil	17%	25 lbs/in (438 N/100 mm)	55 oz/in (60 N/100 mm)	36
3939-48MMX54.8M	051131-06975	Silver	54.8 m	48 mm	9 mil	17%	25 lbs/in (438 N/100 mm)	55 oz/in (60 N/100 mm)	24 individually wrapped rolls
3939-72MMX54.8M	021200-85562	Silver	54.8 m	72 mm	9 mil	17%	25 lbs/in (438 N/100 mm)	55 oz/in (60 N/100 mm)	12
3939-96MMX54.8M	021200-85563	Silver	54.8 m	96 mm	9 mil	17%	25 lbs/in (438 N/100 mm)	55 oz/in (60 N/100 mm)	12

PHONE: 800-245-3573 www.3M.com/Electrical