

## 60 A Control System with Type 3R Load Center

### T21000R Series

Can be used as a load center only, or add a heavy-duty mechanical time switch or wiring devices for a complete system.

#### Applications

- Pool/spa equipment • Lights

#### Features

- Comes with 4/8 position breaker base and equipment grounding bar
- Accepts PF1000M, P1403ME, P1353ME, P4043ME, P4243ME, T100M, or RC2000M Series mechanisms
- Accepts many interchangeable type breakers
- Load center dead front has two knockouts for switches or GFCIs
- Mechanism specifications and ratings on page 142
- Wiring devices may be installed in these Load Centers with the use of Standoffs, sold separately below

Model #	Mechanism	Switch	Mechanism Supply Voltage
<b>T21000R</b>	Load Center Only	—	—
<b>T21001R</b>	T101M	SPST	120 VAC, 60 Hz
<b>T21004R</b>	T104M	DPST	240 VAC, 60 Hz

#### Accessories/Replacement

Trippers (1 ON/OFF)	156T1978A
Insulator for Timers	124--00066
Spacer-Standoff, 3" Long - 2 Pack	21T166A
Spacer-Standoff, 3" Long - 4 Pack	21T156A



Ratings	
<b>Load Center Rating</b>	60 A, 120/240 VAC 120/208 VAC, 60 Hz Single Phase, 60 Hz
<b>Operating Voltage</b>	120-240 VAC, 60 Hz
<b>Switch Type</b>	
T21001R	SPST
T21004R	DPST
<b>Resistive</b>	30 A, 120/208/240 VAC
<b>Inductive</b>	30 A, 120/208/240 VAC
<b>Tungsten</b>	30 A, 120/208/240 VAC
<b>Pilot Duty</b>	1000 VA, 120/208/240 VAC
<b>Motor</b>	2 HP, 24 FLA @ 120 VAC 5 HP, 28 FLA @ 240 VAC
<b>Operating Temperature</b>	-40°F to 130°F (-40°C to 54°C)
<b>Load Center Dimensions H x W x D</b>	16 7/8" x 8 7/8" x 4 3/4" (428.6 mm x 225.4 mm x 120.7 mm)
<b>Knockout Dimensions</b>	
Bottom	(5) combination 1/2" - 3/4" and (3) combination 3/4" - 1"
Left	(1) combination 1/2" - 3/4"
Back	(1) combination 1/2" - 3/4" and (1) 3/4" - 1"
Right	(1) 1 3/4" x 2 3/4"
<b>Warranty</b>	1-year