



T101M



T104M201



Ratings	
Heater Control Center	10 A, 250 VAC MAX, 60 Hz
Resistive	40 A @ Varying Voltages, 60 Hz
Inductive	40 A @ Varying Voltages, 60 Hz
Electronic Ballast	16 A, 277 VAC, 60 Hz
Tungsten	40 A @ Varying Voltages, 60 Hz
Pilot Duty	1000 VA @ Varying Voltages, 60 Hz
Max Power Consumption	3 W
Motor	2 HP, 24 FLA @ 120 VAC, 60 Hz, 5 HP, 28 FLA @ 240 VAC, 60 Hz
Operating Temperature	-40° F to 130° F (-40° C to 54° C)
Warranty	1-year

Voltage Ratings

For more details on model numbers/voltage ratings scan the QR code with your smartphone or tablet.



24-Hour Mechanical Time Switch Only

T100 Series

Heavy-duty mechanical time switches control a single load.

Applications

- Indoor/Outdoor Lighting • Signs • Filters • Electric Fences • Fans
- Conveyors • Pool Heaters • Blowers • Pumps • Other Electrical loads

Features

- Highest motor load ratings in the industry
- 12 ON/OFF operations per day
- One ON and one OFF tripper included
- Can be installed in most Intermatic enclosures
- Available with pool heater protection
- Teeter-type terminals for multiple load connections

Model #	Switch	Input Voltage
Without Pool Heater Protection		
T101M	SPST	120 VAC, 60 Hz
T103M	DPST	
T104M	DPST	208-277 VAC, 60 Hz
T106M	SPDT, 1 NO/1 NC	
With Pool Heater Protection		
T104M201	DPST	208-277 VAC, 60 Hz

Accessories/Replacements

Extra/replacement trippers 1 ON and 1 OFF	156T1978A
Extra/replacement trippers 1 ON and 1 OFF	WG1570
Replacement 208-277 VAC, 60 Hz Motor (T104M, T106M, T104M201)	WG1573
Insulator for Timers	124T1952

Don't Forget

Enclosures see page 166-167