

Two-Circuit Portable Outdoor Timers

P1200 Series



Use these convenient plug-in timers instead of hard-wired controls. They offer plug-in receptacles for convenience and ease of use.

Applications

- Above Ground Pool Pumps • Lights • Fountains

Features

- 24-hour with 23 ½-hour MAX ON time
- Timed circuit controlled by timer
- Timed and photocontrol circuit controlled by photocell and timer (P1251P only)
- Built-in GFCI protected circuits and three-prong grounded plug for time switch supply
- Type 3R plastic indoor/outdoor enclosure
- 2 ON/OFF trippers standard
- Accepts up to 12 sets of trippers

Model #	Photocontrol	Rect/Plug	
P1251P	Yes	5-15	
P1261P	No	5-15	

Accessories/Replacements

Trippers - Clip, ON/OFF, 24-Hr	156PB10398A
Light Shield for Button Photocontrol	6LV1352



P1251P

Ratings	
Resistive	15 A, 1800 W, 60 Hz
Tungsten	15 A, 1800 W, 60 Hz
Motor	1 HP, 15 FLA, 90 LRA @ 120 VAC
Dimensions H x W x D	9.375" x 5.5" x 4" (238.1 mm x 139.7 mm x 101.6 mm)
Cord	3 wire, outdoor grade, 24" with grounded plug
Warranty	1-year

Emergency Shut-Off Switch

PA600 Series

Safety switch intended for disconnecting electrical equipment from its power source, quickly and safely, in case of emergency.

Features

- Fits in single-gang junction box
- Rated for outdoor installation
- Disconnects electrical equipment from its power source in case of emergency
- Electrical grade plastic housing
- Beige, powder-coated steel faceplate

Model #	Description
PA600	Emergency Shut-Off Switch



PA600

Ratings	
Operating Voltage	120-240 VAC, 60 Hz
Switch Type	DPST
Resistive	20 A, 60 Hz
Motor	1 HP, 120 VAC, 60 Hz, 3 HP, 240 VAC, 60 Hz

Fireman Switch

156T4042A

Features

- Coordinated control for pool/spa heaters and filter pumps
- Turns OFF gas pool/spa heater before filter pump shuts down to extend heater life
- 10 A, 250 VAC MAX

Model #	Description
156T4042A	Fireman Switch



156T4042A