

## INCANDESCENT | Medium, Mogul and Candelabra

### Medium, Mogul and Candelabra Base Incandescent Lampholders

#### Features and Benefits

- Medium-to-medium extenders available in phenolic and porcelain
- Two-piece surface-type lampholders have concealed wiring terminals with wireways for top and continuous wiring
- All NOM-ANCE certified except where indicated by °

#### Socket Extensions — Single Circuit

##### Medium-Medium

Description	Rating	Cat. No.
2-Piece Porcelain; Mounting Hole 1 3/8" Dia. Extension 1 1/4"	660W 250V	2004*
1-Piece Porcelain; Slotted Mounting Hole, 4-36 Thread 1 5/8" Dia. Extension 1 1/4"	660W 250V	2005
1-Piece Phenolic. Extension 1 3/16"	660W 250V	2006**

\*To be used with porcelain sockets only

\*\*To be used with phenolic sockets only

##### Mogul-Mogul

Description	Rating	Cat. No.
1-Piece Porcelain. Extension 2 3/8"	1500W 600V	8647

#### Socket Adapter

##### Mogul-To-Medium Porcelain

Description	Rating	Cat. No.
1-piece. Meets Fed. Spec. W-L-142a	660W 250V	8681°
Same as above, except 4 KV Pulse-Rated	660W 250V	8681-400°
Mogul to medium base EX26	Open	28681

NOM-ANCE Certified except where indicated by °

##### Flanged Adapter\*

Description	Rating	Cat. No.
Porcelain E26 male screwshell with leads	660W 600V*	165-00P
Same as 165-00P except Phenolic Body	660W 600V*	165-000
Same as 165-000 except with solder terminals, less leads	660W 600V*	165-001
Porcelain 4KV Pulse Rated	165-450W 600V	165-450°
Phenolic 4KV Pulse Rated	165-400W 600V	165-400°

\*UL Recognized Component, File E13396, Pulse-Rated.

NOM-ANCE Certified except where indicated by °

Continued on next page



2005



8647



8681



165



165-P

