


BULB IDENTIFICATION

Light Center Length (L.C.L.) is the distance from the center of the light source to the following point for the base used:
Screw bases...bottom base contact; Bayonet candelabra and medium bayonet...top of base pins.



Bulb size – Max. Diameter (Divide by 8)

A-21 – $21/8 = 2\ 5/8$ " Dia.

G-40 – $40/8 = 5$ " Dia.

T-12 – $12/8 = 1\ 1/2$ " Dia.

PS-30 – $30/8 = 3\ 3/4$ " Dia.

BASE IDENTIFICATION

Typical bases are shown. One lead-in wire is soldered to the center contact and the other soldered or welded to the upper rim of the base shell. Base shells are typically made of brass or aluminum. ANSI designations are in parentheses.



Candelabra cand. (E12)



Intermediate Inter. (E17)




Medium (E26) & Medium Brass (E26)




3 Contact Medium 3 C Med (E26D)



Double Contact Bayonet D.C. Bay (BA15D)



Mogul Screw




3 Contact Mogul



Medium Skirted Med. Skirt (E26/50x39)

FILAMENT IDENTIFICATION

A FILAMENT designation consists of a prefix letter to indicate whether the wire is straight or coiled, and a number to indicate the arrangement of the filament on the supports. Prefix letters include: C (coiled) – wire is wound into a helical coil or it may be deeply fluted; CC (coiled coil) – wire is wound into a helical coil and this coiled wire again wound into a helical coil.



C-8 CC-8



C-9 CC-9




C-6 CC-6



C-2V CC-2V




C-7A CC-7A



C-11V



C-11 CC-11



C-17




C-2R



C-7

ADDITIONAL INFORMATION

Lamps listed 115-125 volts (design voltage 120), 120-130 volts (design voltage 125), 125-130 volts (design voltage 130) and 230-250 volts (design voltage 240) are intended for use on circuits normally varying within these voltage limits.



Finishes

W or SW - Soft White

DAY - Daylight®

Y - Yellow

B - Blue

R - Red

G - Green

A - Amber

IC - Iridescent clear

FL - Flood

SP - Spot

IF - Inside frost

AIC - Amber iridescent clear

INCANDESCENT LAMP SHAPES

A bulb designation consists of a letter(s) to indicate the shape and a figure to indicate the approximate major diameter in eighths of an inch. For example, an F-15 bulb is a flame-shape, 15/8 of an inch or 1-7/8 inches in diameter.



HOW TO READ PRODUCT INFORMATION – INCANDESCENT

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Avg Rated Life (hrs)	CCT CRI	Lumens	Filament	Legislation Impact	Notes
Bulb		Describes the shape of the envelope followed by the lamp's major diameter given in eighths of an inch. See page 39: Incandescent Lamps.											
Base		See page 38: Base Identification.											
Symbols & Footnotes		All symbols and footnotes that apply to a specific product will appear in this space. The explanations of the symbols and footnotes are at the end of the incandescent section.											
Ordering Abbreviation		A text description of the lamp. See below for several examples and explanations of some of the codes.											
Lumens, Beam Angle, CBCP		These columns may contain data for any of these values.											

HOW TO READ ORDERING ABBREVIATIONS

40B10C/CRYSTAL/DL/BL/2PK		60A/DL/SW/2PK/RP		65BR30/DL/FL/RP	
40	Nominal lamp wattage	60	Nominal lamp wattage	65	Nominal lamp wattage
B	Bulb shape	A	Bulb shape	BR	Bulb shape
10	Bulb size in 8th's of an inch	DL	Double Life lamp	30	Bulb size in 8th's of an inch
C	Candelabra base	SW	Soft white	DL	Double Life lamp
CRYSTAL	Crystal texture on bulb glass	2PK	2 lamps per package	FL	Flood beam pattern
DL	Double Life lamp	RP	Retail pack	RP	Retail pack
BL	Blister pack				
2PK	2 lamps per package				

For the current listing of available products and more complete product information, please visit us at www.sylvania.com.



A19 Med



A21 Med

GENERAL PURPOSE INCANDESCENT LAMPS

Incandescent A-Line Lamps for General Illumination, Task and Accent Lighting

General Purpose Incandescent A-Line Lamps

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Average Rated Life (hrs)	CCT (K)	CRI	Lumens	Filament	Notes
25	3.94	Medium	10562	25A/W/RP 120V	120	24	Soft White	2500	2850	100	160	C-9	●●●
			10634	25A/RP 120V	120	24	Inside Frost	2500	2850	100	190	C-9	●●●
			10644	25A 120V	120	120	Inside Frost	2500	2850	100	190	C-9	●●●
			10645	25A 130V	130	120	Inside Frost	2500	2850	100	180	C-9	●●●
25	3.94	Medium Brass	10694	25A/CL 130V	130	120	Clear	2500	2850	100	180	C-9	●
50	4.44	Medium	11428	50A 277V	277	120	Inside Frost	1000	2850	100	475	CC-7A	●●●
75	5.31	Medium Brass	11566	75A21 12V	12	24	Inside Frost	1000	2850	100	1420	C-6	●
100	5.31	Medium	13404	100A21 230V	230	24	Inside Frost	1000	2850	100	1260	C-9	●●●
			13406	100A21 250V	250	24	Inside Frost	1000	2850	100	1230	C-9	●●●
			13397	100A21 277V	277	24	Inside Frost	1000	2850	100	1040	C-7A	●●●
150	5.31	Medium	13101	150A21/W/RP 120V	120	12	Soft White	750	2850	100	2640	CC-8	●●●
			13125	150A21/CL/RP 120V	120	12	Clear	750	2850	100	2740	CC-8	●●●
			13148	150A21/CL 130V	130	48	Clear	750	2850	100	2730	CC-8	●●●
150	6.06	Medium	13041	150A23 120V	120	48	Inside Frost	750	2850	100	2810	CC-8	●●●
200	5.31	Medium	13103	200A21/W/1RP 120V	120	12	Soft White	750	2850	100	3650	CC-8	●●●
			15476	200A21/CL/RP 120V	120	12	Clear	750	2850	100	3880	CC-8	●●●
			15491	200A21/CL 130V	130	48	Clear	750	2850	100	3880	CC-8	●●●
200	5.31	Medium Brass	15555	200A21/99/XL 125V	125	48	Standard Frost	2500	2850	100	2910	CC-8	●
200	5.31	Medium	15543	200A21 130V	130	48	Standard Frost	750	2850	100	3760	CC-8	●●●

3-WAY Incandescent Lamps

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Voltage	Pkg Qty	Finish	Average Rated Life (hrs)	CCT (K)	CRI	Lumens	Filament	Notes
15 135 150	5.31	3CONTACT Medium Aluminum	18009	15/150A/SECURITYLIGHT 120V	120	12	Soft White	1200	2850	100	80 270 2150	CC-8	▼●●
30 70 100	5.31	3CONTACT Medium Aluminum	19365	30/100A21/DLSW/2/24 120V	120	24	Soft White	2400	2850	100	270 830 1100	CC-8	▼●●
			19380	30/100A21/DLSW/RP 120V	120	12	Soft White	2400	2850	100	270 830 1100	CC-8	▼●●
			19385	30/100A21/W/RP 120V	120	12	Soft White	1200	2850	100	290 915 1205	CC-8	▼●●
50 200 250	5.31	3CONTACT Medium Aluminum	19404	50/250A21/W/RP 120V	120	12	Soft White	1200	2850	100	580 3300 3880	CC-8	▼●●
50 100 150	5.31	3CONTACT Medium Aluminum	18044	50/150A21/DLSW/RP 120V	120	12	Soft White	2400	2850	100	510 1280 1790	CC-8	▼●●
			18458	50/150A21/W/2PK/12 120V	120	12	Soft White	1200	2850	100	580 1540 2120	CC-8	▼●●
			18060	50/150A21/W/RP 120V	120	12	Soft White	1200	2850	100	580 1540 2120	CC-8	▼●●

Specifications subject to change without notice.

Notes on page 53

NOTES FOR INCANDESCENT

Symbol	Description
●	Indicates aluminum base.
⊗	Do not operate in household sockets.
▼	Operate base down.
▲	Operate in any position.
▼	Operate base down to horizontal.
★	Heat resistant, hard glass.
UV	PAR lamps are suitable for indoor and outdoor use.
⊗	Do not operate in paper lined sockets.
♻️	This ECOLOGIC® lamp was designed to pass the Federal TCLP criteria for classification as non-hazardous waste in most states. Disposal regulations may vary; check local and state regulations.

Footnote	Description
1	Should not be used in equipment where base temperature will exceed 500°F.
2	Designed for service other than illumination.
3	Operate only in porcelain sockets.
4	Should be shielded against moisture falling on bulb.
5	Not recommended for use in enclosed close-fitting housings.
6	Not for use in ceiling fan fixtures.
7	Per Title 20 Section 1605.3(m) of the California Code of Regulations, this lamp may not be sold or offered for sale in the state of California for use in traffic signals.
8	Indefinite long life. Designed for life in excess of 10,000 hours. In-service life depends upon burning conditions.
9	Average laboratory life is 200 hours for vacuum cleaner and 600 hours for sewing machine services.
10	Operation of lamp in any position other than base up may result in some loss of protective coating.
11	A protective shield must be used external to the lamp.
12	In base up operation, heat may eventually deteriorate paper-lined or plastic sockets.
13	For use in ceiling fans.
14	Can be operated in any position.
15	May not give satisfactory performance if any accessory lighting equipment touches the glass bulb.
16	For use only with heat-resisting connector and with bulb supported by bulb rim or metal shell of base.