

WIRE LENGTH

COMMERCIAL AND INDUSTRIAL GRADE RECEPTACLES

PlugTail® Connectors & Tester



PTRA6STR PTRA6STRBP PTRA6STRG PTTESTER

Features

- Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.
- Large crimped and welded brass contacts snugly terminate on device blade terminals.
- Pre-stripped connector leads fasten to conductors, easier than standard pigtails.
- Available in any wire length up to 25 inches, use Configurable Solutions to order.
- Audible snapping latch assures connection, allows release.

PT TESTER

- Ensures proper connections and power presence at both rough-in and deviceout stages during P&S PlugTail Device installation.
- Fast, easy identification of circuit connections.
- Easy-to-see indicator lights.
- Sturdy construction for long-term dependability.
- Helps prevent call backs.
- Ensures proper wiring.

CATALOG NUMBER	WIRE TYPE	CONNECTOR HEAD	WIRE LENGTH
PLUGTAIL CONNECTO	RS – RIGHT ANGL	.E	
PTRA6SOL	Solid		6"
PTRA6STR	Stranded		6"
PTRA6SOLB25	Solid		25"
PTRA6STRB25	Stranded		25"
NAFTA-COMPLIANT P	LUGTAIL CONNEC	CTORS - RIGHT A	NGLE
PTRA6SOLNA	Solid		6"
PTRA6STRNABL	Stranded	Blue	6"
PTRA6STRXBB	Stranded		6"
PTRA6STRNARED	Stranded	Red	6"

PTRA6SOLBP	Solid	6"
PTRA6STRBP	Stranded	6"
PLUGTAIL CONNECTOR	RS - RIGHT ANGLE WITH 0	ROUND SCREW*
PTRA6SOLG	Solid	6"
PTRA6STRG	Stranded	6"
Also NAFTA-Complian	t.	

PLUGTAIL CONNECTORS - RIGHT ANGLE WITH WAGO CONNECTORS*

CATALOG NUMBER WIRE TYPE

CATALOG NUMBER	DESCRIPTION	
P&S PLUGTAIL® TESTER		
PTTESTER	Red PlugTail Tester for Receptacles and Tails	