



## Pass and Seymour

Construction Spec Grade Receptacles, Back & Side Wire, 15A, 125V, Gray  
Part No. CRB5262GRY



Construction Spec Grade Duplex Receptacle Back & Side Wire 15amp 125volt Light Almond

### Features & Benefits

Corrosion-resistant, plated steel strap locked in to face and back body to resist pulling away from face/body assembly.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

8 hole internal screw-pressure-plate back wire terminals accept #10 - #14 AWG solid or stranded copper or copper-clad conductors.

Tri-drive terminal and mounting screws.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

.032 inch thick, brass, triple-wipe power contacts for lasting retention.

Impact-resistant nylon face and thermoplastic back body.

Terminal compartments isolated from each other for positive conductor containment.

Auto-ground clip assures positive ground.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

### Specifications

#### General Info

|                   |                         |              |                |
|-------------------|-------------------------|--------------|----------------|
| Color             | Gray                    | UPC Number   | 785007210194   |
| Country Of Origin | Mexico                  | Product Line | Pass & Seymour |
| Standard          | UL498, CSA C22.2 No. 42 |              |                |

#### Listing Agencies / 3rd Party Agencies

|              |     |
|--------------|-----|
| cULus Listed | Yes |
|--------------|-----|

#### Technical Information

|                    |   |                          |                          |
|--------------------|---|--------------------------|--------------------------|
| Number of Poles    | Double Pole   | Voltage                  | 125 V                    |
| Connection         | Back and side wire  | Dielectric Strength      | Withstands 2000V minimum |
| Temperature Rating | Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact | Wire Size                | #14 - #10                |
| Number of Wires    | 3   | Environmental Conditions | Flammability: UL94 V2    |