SWITCHES

Hard Use Specification Grade Switches 15 & 20A, 120/277VAC



Features

- · One-piece brass alloy contact arm for reliable electrical performance.
- · One-piece steel strap with integral ground is plated for corrsion resistance.
- · High strength thermoplastic polycarbonate toggle resists breaking and chipping under heavy abuse.
- Heavy-duty toggle bumpers for smooth and quiet operation.
- Back body made of glass-reinforced nylon.
- Locking support provides resistance to face and back body separation.
- Rated for #14-#10 AWG copper or copperclad wire.
- Cam designed for fast make with positive break action to minimize arcing and prolong switch life.
- · Oversized silver alloy contacts for longer

dependable switch life.

- · Tri-drive terminal and mounting screws.
- Auto-ground clip assures positive ground.
- Posted, ready-to-wire terminal screws for more productive side wire terminations.
- External back-wire pressure plates on Hard Use models make for faster, easier terminations.

Hard Use Specification Grade Back & Side Wire

CATALOG NUMBER				RATING			3RD PARTY COMPLIANCE	
CATALOG NUMBER							•	
SINGLE POLE	DOUBLE POLE	THREE-WAY	FOUR-WAY	Α.	VAC	COLOR	։(♠) ⊪ UL20	FSUL WS896
SINGLE FOLE	DOUBLE FOLE	I II I	FOUN-WAT	Α.	VAC	COLON	ULZU	W3030
CSB15AC1I	CSB15AC2I	CSB15AC3I	CSB15AC4I	15	120/277	lvory	•	•
CSB15AC1W	CSB15AC2W	CSB15AC3W	CSB15AC4W	15	120/277	White	•	•
CSB15AC1	CSB15AC2	CSB15AC3	CSB15AC4	15	120/277	Brown	•	•
CSB15AC1GRY	CSB15AC2GRY	CSB15AC3GRY	CSB15AC4GRY	15	120/277	Gray	•	•
CSB15AC1LA	CSB15AC2LA	CSB15AC3LA	CSB15AC4LA	15	120/277	Light Almond	•	•
CSB20AC1I	CSB20AC2I	CSB20AC3I	CSB20AC4I	20	120/277	lvory	•	•
CSB20AC1W	CSB20AC2W	CSB20AC3W	CSB20AC4W	20	120/277	White	•	•
CSB20AC1	CSB20AC2	CSB20AC3	CSB20AC4	20	120/277	Brown	•	•
CSB20AC1BK		CSB20AC3BK		20	120/277	Black	•	•
CSB20AC1GRY	CSB20AC2GRY	CSB20AC3GRY	CSB20AC4GRY	20	120/277	Gray	•	•
CSB20AC1LA	CSB20AC2LA	CSB20AC3LA	CSB20AC4LA	20	120/277	Light Almond	•	•

For Bulk Packaging Solutions consult factory.