


SWITCHES

Commercial Specification Grade Switches 15 & 20A, 120/277VAC



CS15AC1W



CS15AC3W



CS20AC1W



CS20AC3W

Features

- One-piece brass alloy contact arm for reliable electrical performance.
- One-piece steel strap with integral ground is plated for corrosion resistance.
- High strength thermoplastic polycarbonate toggle resists breaking and chipping under heavy abuse.
- Heavy-duty toggle bumpers for smooth and quiet operation.
- Back body made of glass-reinforced nylon.
- Locking support provides resistance to face and back body separation.
- Rated for #14-#10 AWG copper or copper-clad wire.
- Cam designed for fast make with positive break action to minimize arcing and prolong switch life.
- Oversized silver alloy contacts for longer dependable switch life.
- Tri-drive terminal and mounting screws.
- Auto-ground clip assures positive ground.
- Posted, ready-to-wire terminal screws for more productive side wire terminations.
- External back-wire pressure plates on Hard Use models make for faster, easier terminations.

Commercial Specification Grade Side Wire

CATALOG NUMBER		RATING		COLOR	3RD PARTY COMPLIANCE	
SINGLE POLE	THREE-WAY	A.	VAC		UL20	FSUL WS896
CS15AC1I	CS15AC3I	15	120/277	Ivory	▪	▪
CS15AC1W	CS15AC3W	15	120/277	White	▪	▪
CS15AC1	CS15AC3	15	120/277	Brown	▪	▪
CS15AC1GRY	CS15AC3GRY	15	120/277	Gray	▪	▪
CS15AC1BK	CS15AC3BK	15	120/277	Black	▪	▪
CS15AC1LA	CS15AC3LA	15	120/277	Light Almond	▪	▪
CS20AC1I	CS20AC3I	20	120/277	Ivory	▪	▪
CS20AC1W	CS20AC3W	20	120/277	White	▪	▪
CS20AC1	CS20AC3	20	120/277	Brown	▪	▪
CS20AC1GRY	CS20AC3GRY	20	120/277	Gray	▪	▪
CS20AC1LA	CS20AC3LA	20	120/277	Light Almond	▪	▪

For Bulk Packaging Solutions consult factory.