


TURNLOK® LOCKING DEVICES


20 Amp NEMA L2120, L2220 & L2320 4 Pole, 5 Wire 20A, 3ØY, 120/208, 277/480 & 347/600V




20A Receptacle



20A Connector






20A Plug



20A Flanged Inlet & Outlet

CATALOG NUMBER	RATING		DESCRIPTION/COLOR	CORD DIAMETER	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.				 UL498	FSUL WC596	 CSA
RECEPTACLES								
L2120R	20	3øY, 120/208	Single Receptacle, Black		L21-20R	•	•	•
L2120RBL	20	3øY, 120/208	Single Receptacle, Blue		L21-20R	•	•	•
IGL2120R	20	3øY, 120/208	Single Receptacle, Orange, Isolated Ground		L21-20R	•		•
L2220R	20	3øY, 277/480	Single Receptacle, Black		L22-20R	•	•	•
IGL2220R	20	3øY, 277/480	Single Receptacle, Orange, Isolated Ground		L22-20R	•		•
L2320R	20	3øY, 347/600	Single Receptacle, Black		L23-20R	•	•	•
IGL2320R	20	3øY, 347/600	Single Receptacle, Orange, Isolated Ground		L23-20R	•		•
CONNECTORS IP20 SUITABILITY								
L2120C	20	3øY, 120/208	Black Back, White Front Body	.225"-1.150"	L21-20R	•	•	•
L2120CBK	20	3øY, 120/208	Black Back, Black Front Body	.225"-1.150"	L21-20R	•	•	•
L2220C	20	3øY, 277/480	Black Back, White Front Body	.225"-1.150"	L22-20R	•	•	•
L2320C	20	3øY, 347/600	Black Back, White Front Body	.225"-1.150"	L23-20R	•	•	•
PLUGS IP20 SUITABILITY								
L2120P	20	3øY, 120/208	Black Back, White Front Body	.225"-1.150"	L21-20P	•	•	•
L2120PBK	20	3øY, 120/208	Black Back, Black Front Body	.225"-1.150"	L21-20P	•	•	•
L2220P	20	3øY, 277/480	Black Back, White Front Body	.225"-1.150"	L22-20P	•	•	•
L2320P	20	3øY, 347/600	Black Back, White Front Body	.225"-1.150"	L23-20P	•	•	•
FLANGED INLETS & OUTLETS								
L2120FI	20	3øY, 120/208	Gray Inlet		L21-20P	•		•
L2120FO	20	3øY, 120/208	Gray Outlet		L21-20R	•		•
L2220FI	20	3øY, 277/480	Gray Inlet		L22-20P	•		•
L2220FIBK	20	3øY, 277/480	Black Inlet		L22-20P	•		•
L2220FO	20	3øY, 277/480	Gray Outlet		L22-20R	•		•
L2220FOBK	20	3øY, 277/480	Black Outlet		L22-20R	•		•
L2320FI	20	3øY, 347/600	Gray Inlet		L23-20P	•		•
L2320FO	20	3øY, 347/600	Gray Outlet		L23-20R	•		•



Reference pages 252 and 253 for Accessories.

TURNLOK® LOCKING DEVICES

NEMA Configurations

Locking Plugs & Receptacles

		15 AMPERE		20 AMPERE		30 AMPERE	
		RECEPTACLE	PLUG	RECEPTACLE	PLUG	RECEPTACLE	PLUG
2 POLE, 2 WIRE NON-GROUNDING							
125V	L1	L1-15R	L1-15P				
250V	L2			L2-20R	L2-20P		
2 POLE, 3 WIRE GROUNDING							
125V	L5	L5-15R	L5-15P	L5-20R	L5-20P	L5-30R	5-30P
250V	L6	L6-15R	L6-15P	L6-20R	L6-20P	L6-30R	6-30P
277VAC	L7	L7-15R	L7-15P	L7-20R	L7-20P	L7-30R	7-30P
347VAC	L24			L24-20R	L24-20P		
480VAC	L8			L8-20R	L8-20P	L8-30R	L8-30P
600VAC	L9			L9-20R	L9-20P	L9-30R	L9-30P
3 POLE, 3 WIRE NON-GROUNDING							
125/250V	L10			L10-20R	L10-20P	L10-30R	L10-30P
3ø250V	L11			L11-20R	L11-20P	L11-30R	L11-30P
3ø480V	L12			L12-20R	L12-20P	L12-30R	L12-30P
3ø600V	L13					L13-30R	L13-30P
3 POLE, 4 WIRE GROUNDING							
125/250V	L14			L14-20R	L14-20P	L14-30R	L14-30P
3ø250V	L15			L15-20R	L15-20P	L15-30R	L15-30P
3ø480V	L16			L16-20R	L16-20P	L16-30R	L16-30P
3ø600V	L17					L17-30R	L17-30P
4 POLE, 4 WIRE NON-GROUNDING							
3øY 120/208V	L18			L18-20R	L18-20P	L18-30R	L18-30P
3øY 277/480V	L19			L19-20R	L19-20P	L19-30R	L19-30P
3øY 347/600V	L20			L20-20R	L20-20P	L20-30R	L20-30P
4 POLE, 5 WIRE GROUNDING							
3øY 120/208V	L21			L21-20R	L21-20P	L21-30R	L21-30P
3øY 277/480V	L22			L22-20R	L22-20P	L22-30R	L22-30P
3øY 347/600V	L23			L23-20R	L23-20P	L23-30R	L23-30P

Midget - Locking


		15 AMPERE	
		RECEPTACLE	PLUG
2 POLE, 2 WIRE NON-GROUNDING			
125V	ML1	ML-1R	ML-1P
2 POLE, 3 WIRE GROUNDING			
125V	ML2	ML-2R	ML-2P
3 POLE, 3 WIRE NON-GROUNDING			
125/250V	ML3	ML-3R	ML-3P

Labels & Their Meaning

X, Y, Z	Hot Lead
W	Neutral Lead
G	Grounding Lead

Open Slots

Indicate receptacle configurations (female).



Closed Slots

Indicate plug blade configurations (male).

