



TURNLOK® LOCKING DEVICES


30 Amp NEMA L830 & L930 2 Pole, 3 Wire 30A, 480 & 600V




30A Receptacle




30A Connector





30A Plug



30A Flanged Inlet & Outlet



CATALOG NUMBER	RATING		DESCRIPTION/COLOR	CORD DIAMETER	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.						
						UL498	WC596	CSA
RECEPTACLES								
L830R	30	480	Single Receptacle, Black		L8-30R	•	•	•
L930R	30	600	Single Receptacle, Black		L9-30R	•	•	•
CONNECTORS IP20 SUITABILITY								
L830C	30	480	Black Back, White Front Body	.225"-1.150"	L8-30R	•	•	•
L930C	30	600	Black Back, White Front Body	.225"-1.150"	L9-30R	•	•	•
PLUGS IP20 SUITABILITY								
L830P	30	480	Black Back, White Front Body	.225"-1.150"	L8-30P	•	•	•
L930P	30	600	Black Back, White Front Body	.225"-1.150"	L9-30P	•	•	•
FLANGED INLETS & OUTLETS								
L830FI	30	480	Gray Inlet		L8-30P	•		•
L830FO	30	480	Gray Outlet		L8-30R	•		•
L930FI	30	600	Gray Inlet		L9-30P	•		•
L930FO	30	600	Gray Outlet		L9-30R	•		•



Reference pages 252 and 253 for Accessories.

CATALOG NUMBER	DESCRIPTION	COLOR
WEATHERPROOF COVER		
WPG2	Cover for 20 and 30A Turnlok Flanged Inlets and Outlets	Gray
STAINLESS STEEL WALL PLATE		
SS720	Wall Plate for Locking Receptacles	302/304 S/S



SS720

All devices listed on this page conform to NEMA WD-1 and WD-6.

designed to be better.