


TURNLOK® LOCKING DEVICES

30 Amp NEMA L1830, L1930 & L2030


4 Pole, 4 Wire Non-Grounding 30A, 3ØY, 120/208, 277/480 & 347/600V




30A Receptacle




30A Connector






30A Plug



30A Flanged Inlet & Outlet



CATALOG NUMBER	RATING		DESCRIPTION/COLOR	CORD DIAMETER	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE
	A.	V.				 UL498
RECEPTACLES						
L1830R	30	3øY, 120/208	Single Receptacle, Black		L18-30R	•
L1930R	30	3øY, 277/480	Single Receptacle, Black		L19-30R	•
L2030R	30	3øY, 347/600	Single Receptacle, Black		L20-30R	•
CONNECTORS IP20 SUITABILITY						
L1830C	30	3øY, 120/208	Black Back, White Front Body	.225"-1.150"	L18-30R	•
L1930C	30	3øY, 277/480	Black Back, White Front Body	.225"-1.150"	L19-30R	•
L2030C	30	3øY, 347/600	Black Back, White Front Body	.225"-1.150"	L20-30R	•
PLUGS IP20 SUITABILITY						
L1830P	30	3øY, 120/208	Black Back, White Front Body	.225"-1.150"	L18-30P	•
L1930P	30	3øY, 277/480	Black Back, White Front Body	.225"-1.150"	L19-30P	•
L2030P	30	3øY, 347/600	Black Back, White Front Body	.225"-1.150"	L20-30P	•
FLANGED INLETS & OUTLETS						
L1830FI	30	3øY, 120/208	Gray Inlet		L18-30P	•
L1830FO	30	3øY, 120/208	Gray Outlet		L18-30R	•
L1930FI	30	3øY, 277/480	Gray Inlet		L19-30P	•
L1930FO	30	3øY, 277/480	Gray Outlet		L19-30R	•
L2030FI	30	3øY, 347/600	Gray Inlet		L20-30P	•
L2030FO	30	3øY, 347/600	Gray Outlet		L20-30R	•



Reference pages 252 and 253 for Accessories.

CATALOG NUMBER	DESCRIPTION	COLOR
WEATHERPROOF COVER		
WPG2	Cover for 20 and 30A Turnlok Flanged Inlets and Outlets	Gray
STAINLESS STEEL WALL PLATE		
SS720	Wall Plate for Locking Receptacles	302/304 S/S



WPG2

All devices listed on this page conform to NEMA WD-1 and WD-6.

designed to be better.

TURNLOK® LOCKING DEVICES

NEMA Configurations

Locking Plugs & Receptacles

		15 AMPERE		20 AMPERE		30 AMPERE	
		RECEPTACLE	PLUG	RECEPTACLE	PLUG	RECEPTACLE	PLUG
2 POLE, 2 WIRE NON-GROUNDING							
125V	L1	L1-15R	L1-15P				
250V	L2			L2-20R	L2-20P		
2 POLE, 3 WIRE GROUNDING							
125V	L5	L5-15R	L5-15P	L5-20R	L5-20P	L5-30R	5-30P
250V	L6	L6-15R	L6-15P	L6-20R	L6-20P	L6-30R	6-30P
277VAC	L7	L7-15R	L7-15P	L7-20R	L7-20P	L7-30R	7-30P
347VAC	L24			L24-20R	L24-20P		
480VAC	L8			L8-20R	L8-20P	L8-30R	L8-30P
600VAC	L9			L9-20R	L9-20P	L9-30R	L9-30P
3 POLE, 3 WIRE NON-GROUNDING							
125/250V	L10			L10-20R	L10-20P	L10-30R	L10-30P
3ø250V	L11			L11-20R	L11-20P	L11-30R	L11-30P
3ø480V	L12			L12-20R	L12-20P	L12-30R	L12-30P
3ø600V	L13					L13-30R	L13-30P
3 POLE, 4 WIRE GROUNDING							
125/250V	L14			L14-20R	L14-20P	L14-30R	L14-30P
3ø250V	L15			L15-20R	L15-20P	L15-30R	L15-30P
3ø480V	L16			L16-20R	L16-20P	L16-30R	L16-30P
3ø600V	L17					L17-30R	L17-30P
4 POLE, 4 WIRE NON-GROUNDING							
3øY 120/208V	L18			L18-20R	L18-20P	L18-30R	L18-30P
3øY 277/480V	L19			L19-20R	L19-20P	L19-30R	L19-30P
3øY 347/600V	L20			L20-20R	L20-20P	L20-30R	L20-30P
4 POLE, 5 WIRE GROUNDING							
3øY 120/208V	L21			L21-20R	L21-20P	L21-30R	L21-30P
3øY 277/480V	L22			L22-20R	L22-20P	L22-30R	L22-30P
3øY 347/600V	L23			L23-20R	L23-20P	L23-30R	L23-30P

Midget - Locking


		15 AMPERE	
		RECEPTACLE	PLUG
2 POLE, 2 WIRE NON-GROUNDING			
125V	ML1	ML-1R	ML-1P
2 POLE, 3 WIRE GROUNDING			
125V	ML2	ML-2R	ML-2P
3 POLE, 3 WIRE NON-GROUNDING			
125/250V	ML3	ML-3R	ML-3P

Labels & Their Meaning

X, Y, Z	Hot Lead
W	Neutral Lead
G	Grounding Lead

Open Slots

Indicate receptacle configurations (female).



Closed Slots

Indicate plug blade configurations (male).

