


TURNLOK® LOCKING DEVICES

30 Amp NEMA L1830, L1930 & L2030


4 Pole, 4 Wire Non-Grounding 30A, 3ØY, 120/208, 277/480 & 347/600V




30A Receptacle




30A Connector






30A Plug



30A Flanged Inlet & Outlet



CATALOG NUMBER	RATING		DESCRIPTION/COLOR	CORD DIAMETER	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE
	A.	V.				 UL498
RECEPTACLES						
L1830R	30	3øY, 120/208	Single Receptacle, Black		L18-30R	•
L1930R	30	3øY, 277/480	Single Receptacle, Black		L19-30R	•
L2030R	30	3øY, 347/600	Single Receptacle, Black		L20-30R	•
CONNECTORS IP20 SUITABILITY						
L1830C	30	3øY, 120/208	Black Back, White Front Body	.225"-1.150"	L18-30R	•
L1930C	30	3øY, 277/480	Black Back, White Front Body	.225"-1.150"	L19-30R	•
L2030C	30	3øY, 347/600	Black Back, White Front Body	.225"-1.150"	L20-30R	•
PLUGS IP20 SUITABILITY						
L1830P	30	3øY, 120/208	Black Back, White Front Body	.225"-1.150"	L18-30P	•
L1930P	30	3øY, 277/480	Black Back, White Front Body	.225"-1.150"	L19-30P	•
L2030P	30	3øY, 347/600	Black Back, White Front Body	.225"-1.150"	L20-30P	•
FLANGED INLETS & OUTLETS						
L1830FI	30	3øY, 120/208	Gray Inlet		L18-30P	•
L1830FO	30	3øY, 120/208	Gray Outlet		L18-30R	•
L1930FI	30	3øY, 277/480	Gray Inlet		L19-30P	•
L1930FO	30	3øY, 277/480	Gray Outlet		L19-30R	•
L2030FI	30	3øY, 347/600	Gray Inlet		L20-30P	•
L2030FO	30	3øY, 347/600	Gray Outlet		L20-30R	•



Reference pages 252 and 253 for Accessories.

CATALOG NUMBER	DESCRIPTION	COLOR
WEATHERPROOF COVER		
WPG2	Cover for 20 and 30A Turnlok Flanged Inlets and Outlets	Gray
STAINLESS STEEL WALL PLATE		
SS720	Wall Plate for Locking Receptacles	302/304 S/S



WPG2

All devices listed on this page conform to NEMA WD-1 and WD-6.

designed to be better.