

FLEXCOR® SUPPORT GRIPS

Support Grips Standard-Duty, Closed Mesh


Description

Standard closed mesh support grips are designed for loads up to 600 lbs. and vertical runs of no more than 100 ft. They are available in a variety of eye styles and cable ranges for supporting electrical and fiber optic cable, metal rods, and tubing. Closed mesh support grips are used when the end of the cable is accessible. Support grips are woven of corrosion-resistant tinned-bronze or stainless steel wire.

CATALOG NUMBER STAINLESS STEEL	CABLE DIAMETER RANGE	BALE LENGTH	MESH LENGTH	APPROXIMATE BREAK STRENGTH*
STANDARD-DUTY, CLOSED MESH, SINGLE EYE GRIPS				
FC050U	0.50"-0.62"	7"	10"	567 lbs.
FC062U	0.63"-0.74"	8"	10"	890 lbs.
FC075U	0.75"-0.99"	21"	13"	1,040 lbs.
FC100U	1.00"-1.24"	9"	13.5"	1,700 lbs.
FC125U	1.25"-1.49"	10"	15"	1,700 lbs.
FC150U	1.50"-1.74"	12"	16.5"	1,700 lbs.
FC175U	1.75"-1.99"	14"	20"	2,640 lbs.
FC200U	2.00"-2.49"	16"	21"	3,760 lbs.
FC250U	2.50"-2.99"	18"	24"	3,760 lbs.
FC300U	3.00"-3.49"	21"	26"	5,040 lbs.
STANDARD-DUTY, CLOSED MESH, DOUBLE EYE GRIPS				
FC050UU	0.50"-0.62"	4.3"	9.7"	512 lbs.
FC062UU	0.63"-0.74"	4.3"	9.7"	740 lbs.
FC075UU	0.74"-0.99"	4"	13"	1,000 lbs.
FC100UU	1.00"-1.24"	5"	15"	1,540 lbs.
FC125UU	1.25"-1.49"	5"	16.5"	2,010 lbs.
FC150UU	1.50"-1.74"	5"	20"	3,230 lbs.
FC175UU	1.75"-1.99"	6"	21"	3,230 lbs.
FC200UU	2.00"-2.49"	6"	24"	4,000 lbs.
FC250UU	2.50"-2.99"	6"	26"	4,000 lbs.
STANDARD-DUTY, CLOSED MESH, OFFSET EYE GRIPS				
FC050OF	0.50"-0.62"	5"	10"	512 lbs.
FC062OF	0.63"-0.74"	5.5"	10"	740 lbs.
FC075OF	0.74"-0.99"	5.5"	13"	1,000 lbs.
FC100OF	1.00"-1.24"	6.5"	14"	1,540 lbs.
FC125OF	1.25"-1.49"	7"	15.5"	1,540 lbs.
FC150OF	1.50"-1.74"	7"	17"	1,540 lbs.
FC175OF	1.75"-1.99"	8.5"	19.5"	2,010 lbs.
FC200OF	2.00"-2.49"	10.5"	22"	3,230 lbs.
FC250OF	2.50"-2.99"	11"	23"	3,230 lbs.
FC300OF	3.00"-3.49"	13"	25"	4,000 lbs.
FC350OF	3.50"-3.99"	15"	27"	4,000 lbs.
STANDARD-DUTY, CLOSED MESH, LOCKING BALE GRIPS (UNIVERSAL EYE)				
FC050LB	0.50"-0.62"	18"	10"	530 lbs.
FC062LB	0.63"-0.74"	18"	10"	790 lbs.
FC075LB	0.74"-0.99"	18"	13"	1,020 lbs.
FC100LB	1.00"-1.24"	18"	14"	1,610 lbs.
FC125LB	1.25"-1.49"	18"	15"	1,610 lbs.
FC150LB	1.50"-1.74"	18"	17"	1,610 lbs.
FC175LB	1.75"-1.99"	18"	19"	2,150 lbs.
FC200LB	2.00"-2.49"	18"	21"	3,260 lbs.
FC250LB	2.50"-2.99"	18"	23"	3,260 lbs.
FC300LB	3.00"-3.49"	25"	18"	4,900 lbs.
FC350LB	3.50"-3.99"	27"	18"	4,900 lbs.



Single Eye Grips



Double Eye Grips



Offset Eye Grips



Locking Bale Grips
(Universal Eye)

*To determine workload safety factor, divide approximate break strength by 10.
See page 336 for strength information.

Most Flexcor products have UL and/or CSA Approvals.
Please contact factory for approval information.