

RESIDENTIAL RECEPTACLES

Power Outlet Receptacles & Plugs 20, 30, 50 & 60A



Flush Receptacle




Surface Receptacle



Angle Plug



Plug



Wall Plate

Application




Power devices are for use in industrial, institutional, commercial, and certain residential applications to provide higher amperage power to equipment such as air conditioners, copiers, small welders, ranges, and dryers.

Features

- Flush receptacle bodies are molded of arc-resistant plastic.
- All devices are of dead front design.
- Receptacles have double-wipe contacts of high performance copper-based alloy.
- Recommended stainless steel wall plates are listed with each flush receptacle.
- UL Listed for use with aluminum wiring.

RECEPTACLE AMP. RATING	AWG SIZE	MATERIAL
CONDUCTOR SIZE & MATERIAL FOR POWER OUTLET RECEPTACLES		
20A	#14 – #10	Copper/Copper-clad
30A	#10 – #6	Copper/Copper-clad/Aluminum
50A	#10 – #6	Copper/Copper-clad/Aluminum
60A	#8 – #4	Copper/Copper-clad/Aluminum

AMPERE RATING	WITH NON-METALLIC SHEATHED CABLE	WITH CONDUIT
RECOMMENDED BOX SIZES FOR FLUSH RECEPTACLES		
30A	4" sq. x 2-1/8" deep	4-11/16" sq. x 2-1/8" deep
50A	4-11/16" sq. x 2-1/8" deep	2-g deep box (4" sq. x 2-1/2" deep)
60A	4-11/16" sq. x 2-1/8" deep with 1/2" raised ring	2-g deep box (4" sq. x 2-1/2" deep)

DESCRIPTION		COLOR	NYLON	METAL		WALL PLATES RECOMMENDED FOR THE FOLLOWING FLUSH RECEPTACLES	
			TRADEMASTER®	MATERIAL			
ACCESSORIES - FLUSH RECEPTACLE WALL PLATES							
	<ul style="list-style-type: none">• 2.156" hole for 2.125" dia. device• 2 mtg. holes	Ivory	TP724I	Chrome	S384C	2 Pole, 3 Wire Grounded	
		White	TP724W			3801	3804
		Brown	TP724			3802	3830
		Gray	TP724GRY				
		Black	TP724BK				
		Light Almond	TP724LA			302S/S	SS724
	<ul style="list-style-type: none">• 2-5/32" hole for 2-1/8" dia. device• 2 mtg. holes			302S/S	SS702	3 Pole, 3 Wire Ungrounded	
						3860	3860
	<ul style="list-style-type: none">• 2.1563" hole for 2.125" dia. device• 4 mtg. holes	Ivory	TP703I	Chrome	S3862C	3 Pole, 4 Wire Ungrounded	
		White	TP703W			3864	5740
		Brown	TP703			3894	5750
		Gray	TP703GRY				5760
		Black	TP703BK				
		Light Almond	TP703LA				