


COMMERCIAL GRADE RECEPTACLES

Heavy-Duty Specification Grade Single Receptacles 15 & 20A, 125 & 250V




5361I

Features

- Corrosion-resistant, plated steel strap locked in to face and back body to resist pulling away from face/body assembly.
- One-piece brass, triple-wipe power contacts for lasting retention.
- Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.
- Impact-resistant nylon face and thermoplastic back body.
- Internal screw-pressure-plate back wire capable of accepting #14 – #10 AWG solid or stranded copper or copper-clad wire.
- Terminal compartments isolated from each other for positive conductor containment.
- Tri-drive terminal and mounting screws.
- Auto-ground clip assures positive ground.


CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE	
	A.	V.			 cULus	FSUL WC596
SINGLE RECEPTACLES BACK & SIDE WIRE						
5261I	15	125	Ivory	5-15R	•	•
5261W	15	125	White	5-15R	•	•
5261	15	125	Brown	5-15R	•	•
5261GRY	15	125	Gray	5-15R	•	•
5261BK	15	125	Black	5-15R	•	•
5261RED	15	125	Red	5-15R	•	•
5261LA	15	125	Light Almond	5-15R	•	•
5361I	20	125	Ivory	5-20R	•	•
5361W	20	125	White	5-20R	•	•
5361	20	125	Brown	5-20R	•	•
5361GRY	20	125	Gray	5-20R	•	•
5361BK	20	125	Black	5-20R	•	•
5361RED	20	125	Red	5-20R	•	•
5361LA	20	125	Light Almond	5-20R	•	•
5671I	15	250	Ivory	6-15R	•	•
5671	15	250	Brown	6-15R	•	•
5671RED	15	250	Red	6-15R	•	•
5671BL	15	250	Blue	6-15R	•	•
5671LA	15	250	Light Almond	6-15R	•	•
5871I	20	250	Ivory	6-20R	•	•
5871W	20	250	White	6-20R	•	•
5871	20	250	Brown	6-20R	•	•
5871GRY	20	250	Gray	6-20R	•	•
5871BK	20	250	Black	6-20R	•	•
5871RED	20	250	Red	6-20R	•	•
5871LA	20	250	Light Almond	6-20R	•	•

2 Pole, 3 Wire



NEMA 5-15R

NEMA 5-20R



NEMA 6-15R

NEMA 6-20R

For Bulk Packaging Solutions consult factory.