


PLUGMOLD® 2000TR SERIES™


Aluminum Plugmold 2000TR Series Ordering Information

Tamper-Resistant Plugmold



PART NUMBERS:


AL20GB306TR (3' (914mm) Length)
AL20GB506TR (5' (1.5m) Length)
AL20GB512TR
AL20GB606TR
AL20GB612TR
AL20GB618TR
AL20GBA606TR
AL20GBA612TR
AL20GBA618TR



AL20GB306TR


Available in 3' (914mm), 5' (1.5m), and 6' (1.8288m) lengths with 6" (152mm), 12" (304.8mm), and 18" (457.2mm) receptacle spacing. 15A tamper-resistant receptacles. 3-wire, #12 THHN (1 hot, 1 neutral, and insulated ground conductor rated for use on 20A circuits). .060" (1.5mm) 6063-T5 extruded aluminum housing with satin anodized finish. Packed 2 per carton. Each unit supplied with one (1) Coupling and two (2) Blank End Fittings.

AL2001 Coupling




Connects adjoining sections of AL2000TR Series Raceway base.

AL2009 Ground Clamp




(Galvanized Steel) Connects equipment grounding conductor to provide additional ground to raceway.

AL2010A Feed Fitting




End fitting with 1/2" (12.7mm) hub adapter.

AL2010B Blank End Fitting




Closes off open end of sections of AL2000TR Series Raceway.

AL2047 Shallow Switch and Receptacle Box



Designed for standard shallow switches and receptacles. Base has open back plate for mounting to existing wall box and solid back plate insert with 1/2" and 3/4" trade size KOs to close opening. Not for use with AL2400 Series Raceway.

AL2051H Box Adapter



Used to feed raceway from existing wall outlet box. Accepts up to 5/8" trade size conduit.