


WORKSTATION POWER SOLUTIONS

Ordering Information

Work Station Power Solutions - Power Only Plug-In Outlet Center Units Ordering Information


Plug-In Outlet Center Units


PART NUMBERS:
UL205BC (6 Foot Cord)

UL205BD (15 Foot Cord)

Eight outlets, rugged gray aluminum housing, 15A. 6' (1.8m) (UL205BC) or 15' (4.6m) (UL205BD) 14/3 SJT black cord with NEMA5-15 plug. Length 13" (330mm). Receptacle center-to-center 1 1/4" (32mm). Snap-on, slide-off mounting.


Plug-In Outlet Center Units


PART NUMBERS:
UL210BC (6 Foot Cord)

UL210BD (15 Foot Cord)

Ten outlets, rugged gray aluminum housing, 15A, lighted switch. 6' (1.8m) (UL210BC) or 15' (4.6m) (UL210BD) 14/3 SJT black cord with NEMA5-15 plug. Length 13" (330mm), width 3 1/2" (89mm). Receptacle center-to-center 1 15/16" (49mm). Keyhole mounting.


Plug-In Outlet Center Units


PART NUMBERS:
UL206BC (6 Foot Cord)

UL206BD (15 Foot Cord)

Six outlets, rugged gray aluminum housing, 15A. 6' (1.8m) (UL206BC) or 15' (4.6m) (UL206BD) 14/3 SJT black cord with NEMA5-15 plug. Length 12 1/4" (311mm). Receptacle center-to-center 1 1/4" (32mm). Snap-on, slide-off mounting.


Plug-In Outlet Center Units


PART NUMBERS:
R610 (6 Foot Cord)

R612 (15 Foot Cord)

Six outlets, putty white aluminum housing, 15A, lighted switch. 6' (1.8m) (R610) or 15' (4.6m) (R612) 14/3 SJT putty white cord with NEMA5-15 plug. Length 12 1/4" (311mm). Receptacle center-to-center 1 1/4" (32mm). Snap-on, slide-off mounting.


Plug-In Outlet Center Units


PART NUMBERS:
UL207BC (6 Foot Cord)

UL207BD (15 Foot Cord)

Six outlets, rugged gray aluminum housing, 15A, lighted switch. 6' (1.8m) (UL207BC) or 15' (4.6m) (UL207BD) 14/3 SJT black cord with NEMA5-15 plug. Length 12 1/4" (311mm). Receptacle center-to-center 1 1/4" (32mm). Snap-on, slide-off mounting.


Plug-In Outlet Center Units


PART NUMBERS:
P6 (6 Foot Cord)

P6-15 (15 Foot Cord)

Six outlets, putty white impact-resistant polymeric housing, 15A, lighted switch, 6' (1.8m) (P6) or 15' (4.6m) (P6-15) 14/3 SJT putty white cord with NEMA5-15 plug. Length 12" (305mm). Receptacle center-to-center 1 1/4" (32mm). Keyhole mounting.


Plug-In Outlet Center Units


PART NUMBERS:
UL218BC (6 Foot Cord)

UL218BD (15 Foot Cord)

Eight outlets, rugged gray aluminum housing, 15A, lighted switch. 6' (1.8m) (UL218BC) or 15' (4.6m) (UL218BD) 14/3 SJT black cord with NEMA5-15 plug. Length 15" (381mm). Receptacle center-to-center 1 1/4" (32mm). Snap-on, slide-off mounting.

Plug-In Outlet Center Units


PART NUMBERS:
UL1090BC (6 Foot Cord)

Four outlets, rugged gray aluminum housing, 15A, receptacles rotated 90° and spaced to accommodate transformers. 6' (1.8m) (UL1090BC) 14/3 SJT black cord with NEMA5-15 plug. Length 16" (406mm). Receptacle center-to-center 3" (76mm). Snap-on, slide-off mounting.