


# 4000® SERIES RACEWAY


## 4000 Series Raceway Ordering Information (continued)

### 4001DA Divider Clip (Galvanized)



Required for holding G4000D Divider in place. Use one every 2 1/2' (.762m).

### Seam Clip




PART NUMBERS:

**V4006** (Ivory)

**G4006** (Gray)

Covers seams where two sections of 4000 Series Raceway covers come together.

### Blank End Fitting




PART NUMBERS:

**V4010B** (Ivory)

**G4010B** (Gray)

Closes off open end of 4000 Series Raceway. Has two 1/2" trade size KOs to facilitate end feeding.

### Entrance End Fitting



PART NUMBERS:


**V4010DFO** (Ivory)

**G4010DFO** (Gray)

Full capacity entrance end fitting. Has concentric 3/4", 1", and 1 1/4" trade size KOs on end and bottom for feeding 4000 Series Raceway. Includes removable divider and

1 1/4" (32mm) bend radius control insert for UTP/STP and fiber optic cable installations.

### Flat Elbow




PART NUMBERS:

**V4011** (Ivory)

**G4011** (Gray)

Right angle turns on the same surface.

### Radiused Full Capacity Flat Elbow



PART NUMBERS:


**V4011FO** (Ivory)

**G4011FO** (Gray)

Full capacity 90° flat corner used in divided or undivided applications. 2" (51mm) bend radius control for UTP, STP and fiber optic installations.

Ideal for new installations when the cable is lay-in or pull-through.

### Internal or External 45° Elbow




PART NUMBERS:

**V4012TX** (Ivory)


**G4012TX** (Gray)

Internal or external 45° turns in a run of 4000 Series Raceway. Can also be assembled as an inverted 45° elbow.

Assembled as an external elbow.




### Wall Box Connector



PART NUMBERS:


**V4014A** (Ivory)

**G4014A** (Gray)



Base has two concentric 1", 3/4", and 1/2" trade size KOs, two concentric 1 1/4", and 1" KOs (undivided only), and two rectangular 2 9/16" x 1 11/16" KOs.

### Tee




PART NUMBERS:

**V4015** (Ivory)

**G4015** (Gray)

For branching raceway at right angles. Use with undivided raceway only. Join to raceway run with two pair of 4001A Couplings (not included).

### Divided Tee



PART NUMBERS:

**V4015D** (Ivory)


**G4015D** (Gray)

For branching raceway at right angles. Use with divided raceway only. Join to raceway run with two pair of 4001A Couplings (not included).

# S4000® SERIES RACEWAY


## S4000 Series Raceway Wire Fill Capacities for Communications (continued)

### S4000C150 15" (381mm) Precut Raceway Cover




.040" (1.0mm) stainless steel. Snap-on cover for mounting 9" (229mm) device plates on 24" (610mm) centers.

### S4000C195 19.5" (495mm) Precut Raceway Cover




.040" (1.0mm) stainless steel. Snap-on cover for mounting 4 1/2" (114mm) device plates on 24" (610mm) centers.

### S4000C270 27" (686mm) Precut Raceway Cover




.040" (1.0mm) stainless steel. Snap-on cover for mounting 9" (229mm) device plates on 36" (915mm) centers.

### S4000C315 31.5" (800mm) Precut Raceway Cover




.040" (1.0mm) stainless steel. Snap-on cover for mounting 4 1/2" (114mm) device plates on 36" (915mm) centers.

### S4000C390 39" (990mm) Precut Raceway Cover




.040" (1.0mm) stainless steel. Snap-on cover for mounting 9" (229mm) device plates on 48" (1220mm) centers.

### S4000C435 43.5" (1105mm) Precut Raceway Cover




.040" (1.0mm) stainless steel. Snap-on cover for mounting 4 1/2" (114mm) device plates on 48" (1220mm) centers.

### G4000D Divider




.040" (1.0mm) galvanized steel. Packed ten 5' (1.5m) lengths (50' (15.20m)) per carton. Painted buff on one side to provide compartment identification. 4001DA Divider Clips (not included) are required to hold divider in place.

### 4001DA Divider Clip (Galvanized)




Required for holding G4000D Divider in place. Use one every 2 1/2' (.762m).

### S6008A C-Hanger




Suspends S4000, 4000 or 6000 Series Raceway from a structural ceiling. Designed for use with 3/8" (9.5mm) rod. Hangers should be installed no more than 5' (1.5m) apart along raceway run. Can be bolted back-to-back for dual runs of 3000, 4000 or 6000 Series Raceway.

### S4010B0 Blank End Fitting




Closes off open end of S4000 Base. Use when no end feeding is required. Includes two No. 10-32 ground terminals.

### S4010B1 Blank End Fitting



Closes off open end of S4000 Base. Use when one end feed is required in an undivided installation. Includes one 1/2" - 3/4" trade size KO and two No. 10-32 ground terminals.

### S4010B2 Blank End Fitting



Closes off open end of S4000 Base. Use when end feeds are required for an installation. Includes two 1/2" - 3/4" trade size KOs and two No. 10-32 ground terminals.