WALKERDUCT® SYSTEMS

Quick Selection Guide

Walkerduct Underfloor Duct Systems Service Fitting Compatibility

PRODUCT FAMILY			ACTIV LOCA	ATION		SERVIC APACIT		SERVICE COMPATIBILITY			MATERIAL/COLORS				
		CATALOG NUMBER	Flush	Pedestal	Single Service	Dual Service	Triple Service	Power	Communication	Audio/Visual	Polycarbonate	Aluminum	Brass	Gray	Black
	1200 Series	1204BF													
		1204AL													
		1223BF													
		1223AL													
	525 Series	525A													
		525B													
		525C													
		525D													
		525F													
		25G													
		525H													
		5251													
		525J													
		525RT			•			•	•	•					
		525ACT			•				•			•			
		MP4		•	•				•			•			
	Multiplex	MP8		•	•			•	•	•		•			
				•		•		•	•	•		•			
	Pro Series	MP8-1		•		•		•	•	•		•			
		817B	•		•			•	•				•		
		827B	•			•		•	•				•		
		837B	•				•	•	•				•		
		817PCC	•		•			•	•		•				•
		827PCC	•			•		•	•		•				•
		837PCC	•				•	•	•		•				•
		818TCAL 828TCAL			•							•			
		838TCAL					_								
	PSRC9 Series	PSRC9TC	•		_		•		•				_		
		PSRC9AMDTC													
		PSRC9FFTC													
	Source I	S165B							•						
		S165BLK/BRN													
		S166B													
		S166BLK/BRN													
		S175BLK/BRN													
		CITODEIT/ DIIIV	_												

www.legrand.us/wiremold _____ designed to be better.

SOURCE 1° SERVICE FITTINGS

Compatible with Walkerduct



Source 1° Series Flush Activations offer a wide variety of single-service power and communications for infloor distribution systems. Source I fittings are available in brass or in black or brown polycarbonate finishes. They are ideal for new construction and retrofit projects and can be used as presets or aftersets with Walkerduct and Walkercell systems.


CODE REFERENCE

cULus Listed Underfloor Raceway Fittings:

File E11912, Guide RQKX Meets Article 390 of NEC

Source 1 Series Service Fittings Ordering Information


Double Duplex Power Activation



PART NUMBERS: S175BLK (Black) S175BRN (Brown)

Double duplex polycarbonate assembly, 7/8" to 3 3/8" (22.2mm to 86mm) concrete topping. 15A, 125V receptacles included.


Complete Flush Activation



PART NUMBERS: S166BLK (Black) S166BRN (Brown)

Flush polycarbonate communication slides.


Complete Flush Activation



PART NUMBERS: S165BLK (Black) S165BRN (Brown)

Flush polycarbonate power – single duplex. 15A, 125V receptacles included.

S166B Complete Flush Activation




Flush brass communication (slides). Used for data cable pass-through.

S165B Complete Flush Activation



Flush brass power – single duplex flip lids. May be used with 106 type adapters for data applications.

Carpet Flange



PART NUMBERS: S124BLK (Black) S124BRN (Brown)

Flush polycarbonate carpet flange only with mounting screws.

COLOR OPTIONS







Source 1° Series Service Fittings are available in brass, brown polycarbonate or black as indicated in the part number description.