

30A, 50A and 60A Devices

Residential, Commercial and Industrial Grade Power Devices

Built from durable thermoplastic, Leviton power receptacles — in flush mount, surface mount and panel mount versions — come equipped with heavy-gauge, double-wire copper alloy contacts. To ensure correct and speedy wiring, terminals have ID markings. Flush mount receptacles fit Leviton's wide range of 2.15"-diameter wallplates and mounting hardware is included. Angle plugs are made of tough, heavy-duty nylon for a long dependable service life.

8462-P, 5054 and 279



Features and Benefits

- Heavy-gauge, double-wipe copper alloy contacts
- Easy-to-wire terminals accept up to #4 AWG conductors
- Terminals marked for easy identification and fast wiring
- Flush-mount devices fit two-gang outlet boxes
- Surface-mount devices are commercial grade and have concentric knockouts for 3/4" and 1" conduit and adjustable cord clamp for back and bottom entrance of cable

Angle Plugs

- Rugged cord clamp for secure cable grip accommodates cord diameters from .625" to 1.375" and does not tear conductor jacket
- Made of tough, heavy-duty nylon for long service life
- Devices feature heavy-sectioned dead-front right-angle
- Pressure-clamp terminal design
- Terminals accept up to #4 AWG stranded conductors
- Four-way positioning front module
- Solid brass blades for maximum conductivity

NOTE: Refer to instruction sheets for proper conductor size, material and torque range.

WARNING: Do not use with single-gang wallboxes, single-gang mud rings or single-gang box extenders.

Continued on next page

Continued from previous page

30A and 50A Residential, Commercial and Industrial Grade Power Devices

Rating	Receptacle/Plug Configuration & NEMA No.		Flush Mount Receptacle	Surface Mount Receptacle	Panel Mount Receptacle	Angle Plug	Wallplate Size
2-Pole, 3-Wire, Grounding  							
30A-125V	5-30R 	5-30P 	—	—	—	9530-P 	2.15" Center
30A-125V For Recreation Vehicles Cat. No. W7313 is WR	TT-30R 	TT-30P 	7313/W7313  Cat. No. W7313 is WR	—	—	830-T 	
30A-250V	6-30R 	6-30P 	5372/5372-IG* 	5376 	—	9630-P 	
30A-277V	7-30R 	7-30P 	9730-A 	—	—	—	
50A-125V	5-50R 	5-50P 	5373 	—	—	9550-P 	
50A-250V	6-50R 	6-50P 	5374/5374-IG* 	5378 	—	9650-P 	
50A-277V	7-50R 	7-50P 	9750-A 	—	—	9750-P 	

*Isolated Ground.

Continued on next page

Wallplates

1-Gang

30A and 50A Receptacle,
2.15" dia. hole



Thermoset (Plastic) 80528-W
Thermoplastic (Nylon) 80728-W
Stainless Steel 84028

2-Gang

30A and 50A Receptacle,
2.15" dia. hole



Thermoset (Plastic) 80526-W
Thermoplastic (Nylon) 80726-W
Stainless Steel 84026

See Wallplates section pages **R-9** and **R-10** for complete ordering information.

NOTE: Refer to instruction sheets for proper conductor size, material and torque range.

WARNING: Do not use with single-gang wallboxes, single-gang mud rings or single-gang box extenders.

Traditional Wallplates

Familiar and functional, Leviton traditional wallplates are designed for use with traditional Leviton devices. They represent styles and form factors that have stood the test of time. Their clean lines work in virtually any location, whether in new or retrofit construction, and they install quickly and easily. Leviton offers traditional wallplates in a vast array of colors and configurations.

Sample Traditional Wallplates



Features and Benefits

All Leviton Wallplates

- Easy to clean, smooth finish
- Non-combustible
- Color-matched metal mounting screws supplied
- UL Listed and CSA Certified
- Conforms to NEMA and ANSI standards
- Backed by a limited 10-year warranty (except thermoset wallplates)

Thermoset (Plastic) Wallplates (Residential Grade)

- Designed for high dielectric strength and arc resistance
- Meets or exceeds UL 514 testing requirements
- Resistant to fading, discoloration, grease, oil, organic solvents, moisture and scratches
- Backed by a limited 2-year warranty

Thermoplastic (Nylon) Wallplates (Residential/Commercial Grade)

- Molded thermoplastic for maximum resistance to impact, abrasion, fading and discoloration
- Resistant to mechanical stress associated with high abuse applications

Metal Wallplates (Commercial Grade)

- Rounded edges to prevent injury and wall damage
- Deluxe stainless steel is non-magnetic Type 302, .032" thick — brushed finish
- Standard stainless steel Type 430, .032" thick, also available — brushed finish
- Brass is 70/30 alloy 260, .040" thick — polished or brushed finish

Antimicrobial Treated Wallplates

- Leviton has developed antimicrobial treated wiring devices to help keep the surfaces of our switches and wallplates cleaner.
- An antimicrobial additive helps to inhibit the growth of mold, mildew, fungi and odor-causing bacteria on the surface of the devices in between normal cleanings

Color Choices

Traditional wallplates are offered in a wide range of colors and finishes. To order colors, add suffix to Cat. No.



White
(-W)



Ivory
(-I)



Light Almond
(-T)



Gray
(-G/-GY)



Black
(-E)



Brown
(-/-B)



Blue
(-B)



Orange
(-O)



Red
(-R)



Brushed
Brass



Polished
Brass
(-PB)



Satin-Finish
Stainless
Steel



Aluminum



Chrome

Traditional Wallplates




Power Outlet Receptacles



Continued from previous page





Power Outlet Receptacles

Standard Size Plastic, Nylon and Metal — 2-Gang

		Thermoset (Plastic)		Thermoplastic (Nylon)	Metal	
Description	Color	Cat. No.	Cat. No.	Cat. No.	Material Type	Cat. No.
	White	80526-W	80726-W	80726-W	Aluminum	83026
	Ivory	80526-I	80726-I	80726-I	Gray Painted Steel	4934
	Lt. Almond	80526-T	—	—	Stainless Steel	84026
	Black	80526-BLK	—	—	C-Series 430 S/S	SL703
	Brown	—	80726	80726	C-Series 302/304 S/S	SS703-40
	White	80530-W	—	—	Gray Painted Steel	S701-GY
	Ivory	80530-I	—	—	C-Series 430 S/S	SL701
	Lt. Almond	80530-T	—	—	C-Series 302/304 S/S	SS701-40
	Black	80530-BLK	—	—	Non-Magnetic S/S	S701-40
					Stainless Steel	84022

Note: Use with 278, 279, 5206, 5207, 5371, 5372, 5374

Standard Size Metal — 2-Gang with Centered Opening

		Metal	
Description		Material Type	Cat. No.
 1-Decora®		Non-Magnetic S/S	S746-N
 1-Toggle		Brass Non-Magnetic S/S	81040 84040-40
 1-Duplex		C-Series 430 S/S C-Series 302/304 S/S Non-Magnetic S/S	SL748 SS748-40 84039-40
 1-Outlet 1.406" dia. hole		Non-Magnetic S/S	84092-40

Standard Size Louvre

		Painted Steel	Metal	
Description	Color	Cat. No.	Material Type	Cat. No.
 1-Gang, Center Horizontal, Strap Mount	White	88079	Brass Non-Magnetic S/S	81079 84079-40
 1-Gang Vertical, Strap Mount	White	88080	Brass Non-Magnetic S/S	81080 84080-40
 2-Gang, 2-Louvre, Vertical, Strap Mount			Non-Magnetic S/S	84081-40