

## Appliance Switches

### Features and Benefits

#### Single Pole Pull Chain Switches

- Standard finish of metal chain is nickel
- Standard leads are #18 AWG 105°C plastic, 6" long, stripped 1/2"
- 3 3/4" chain connector, 3' braided cord, end bell
- Bushing 3/8 - 27 x 3/8" long
- Piercing 13/32" dia

#### Door Jamb Switch

- Bushing 15/32-32 x 9/16" long

#### Single Pole Pull Chain Switches

Rating	3A 125VAC-L	6A-125VAC	3A-250VAC	1/4 HP 125/250V
Description	Sequence			Cat. No.
Heavy Duty, Single Circuit, Black and Red Leads	ON-OFF (L1, OFF)			1689-75
Heavy Duty, Two Circuit, Four Positions, Black, Blue, Red Leads	LOW-MED-HIGH-OFF (L1, L2, L1 & 2, OFF)			1689-50
Heavy Duty, Two Speed, Four Positions, Black, Blue, Red Leads	ONE-OFF-TWO-OFF (L1, L2, L3, OFF)			1691-50

Rating	3A-125V	1A-125VT	1A-250V
Description	Sequence		Cat. No.
Compact, Single Circuit, Black Leads	ON-OFF		10097-8

Rating	3A-125VAC-L	6A-125VAC	3A-250VAC
Description	Sequence		Cat. No.
Compact, Single Circuit, Black Leads	ON-OFF		10041-500

#### Push-Button Door Jamb Switch

Rating	3A-125V		
Description	Sequence		Cat. No.
Single Circuit, Momentary, Metal Pushbutton, #18 AWG Leads, with Jamb Box, Mounting Screws and Cover Plate	NORMALLY ON		1865

#### Feed-Through Cord Switch

Rating	3A-125V 1/2 HP 125V			
Description	Sequence	Color	Cat. No.	
Heavy Duty, Single Pole, 18/2 - 16/2 Type SPT-1, SPT-2 or Round Cord 18/2, Type SVT and other cords up to 9/32" outer jacket	ON-OFF	White	5410-W	
		Ivory	5410-I	
		Brown	5410	

#### Miniature Feed-Through Cord Switch

Rating	3A-125V 1/2 HP 125V			
Description	Sequence	Color	Cat. No.	
Miniature Single Pole, Captive Screw (for use with #18 ga. SPT-1 conductors)	ON-OFF	White	423-3W	
		Ivory	423-3I	
		Brown	423-3	



1689-75



10097-8



1865



5410-W



423-3I